

AGRICULTURE TYRES TECHNICAL DATABOOK



2022

MAY 2022

Peace of mind, every time


Kleber

NOTES

Notes section with horizontal dotted lines for writing.

SUMMARY

READING THE TECHNICAL DATA	4
EQUIVALENCE CHART	5
TYRES BY SIZE	7
ROLLING CIRCUMFERENCE CHART	10
LOAD INDEX	14
TRACTORS - HIGH POWER	15
KLEBER TOPKER IF	15
KLEBER TOPKER	19
TRACTORS - LOW & MEDIUM POWER	23
KLEBER GRIPKER	23
KLEBER FITKER	29
KLEBER TRAKER	37
KLEBER SUPER VIGNE	45
KLEBER SUPER 8L	50
KLEBER SUPER G	53
ROW CROP	55
KLEBER CROPKER	55
KLEBER SUPER 3	62
TELEHANDLERS	64
KLEBER LUGKER	64



READING THE TECHNICAL DATA

Rim diameter in inches		Local country & International Product Code					(e) Maximum overall section width on measuring rim in millimeters					(D) Overall diameter in millimeters					(R') Static laden radius in millimeters					(RC) Rolling Circumference in millimeters									
Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)																				
30	IF 600/70R30 165D/161E TL	278892	634	1591	695	4709	DW21B (A)	DW20B (A)	737	468	52																				
(TL) Tubeless																															

EQUIVALENCE CHART

STAGE 1

Identify the relevant SRI using the original size.

Speed Radius Index (SRI) is a parameter used to calculate the theoretical speed of vehicles for homologation procedures by vehicles manufacturers and for the interchangeability of different tyre sizes.

Ø	DIMENSIONS	SRI	Ø	DIMENSIONS	SRI	Ø	DIMENSIONS	SRI	Ø	DIMENSIONS	SRI
16	6.50R16	360	26	480/70R26	650	32	210/95R32 (8.3R32)	575	38	650/85R38	975
	7.50R16	390		23.1-26	750		230/95R32 (9.5R32)	600		680/75R38	925
	250/80R16	390		520/80R26	700		270/95R32 (11.2R32)	625		710/60R38	875
	260/70R16	360		540/65R26	650		320/85R32 (12.4R32)	650		710/70R38	925
	280/65R16	360		580/70R26	675		650/75R32 (24.5R32)	825		710/85R38	1025
	280/70R16	390		620/70R26	725		680/75R32 (30.5LR32)	875		750/65R38	925
18	320/65R16	390		620/75R26	750		680/85R32	925		800/70R38	975
	7.50R18	410		750/50R26	675	34	800/65R32	875	42	900/60R38	975
	280/70R18	410		750/65R26	750		800/70R32	925		230/95R40 (9.5R40)	700
	320/65R18	410	28	9.5R28	550		900/60R32	925		270/95R42 (11.2R42)	750
	340/65R18	425		250/85R28	550		1000/55R32	875		300/95R42 (12.4R42)	800
20	7.50R20	425		280/85R28 (11.2R28)	575		1050/50R32	875		320/90R42	800
	9.5R20	450		320/70R28	575	36	320/85R34	675		480/80R42 (18.4R42)	875
	11.2R20	475		320/85R28 (12.4R28)	600		380/85R34	725		520/85R42 (20.8R42)	925
	12.4R20	500		340/65R28	550		420/85R34 (16.9R34)	750		580/85R42	975
	13.6R20	525		340/85R28 (13.6R28)	625		460/85R34 (18.4R34)	775		620/70R42	925
	14.9LR20	525		360/70R28	600		480/70R34	750		650/65R42	925
	260/80R20	450		380/70R28	625	38	520/70R34	775		650/85R42	1025
	280/70R20	425		380/85R28 (14.9R28)	650		520/75R34	775		710/60R42	925
	280/85R20	475		420/65R28	600		540/65R34	750		710/70R42	975
	300/70R20	450		420/70R28	650		600/60R34	750		710/75R42	1025
	320/70R20	475		420/75R28	650		600/65R34	775	44	900/50R42	925
	320/85R20	500		420/85R28 (16.9R28)	675		620/75R34	825		900/60R42	1025
	340/65R20	450		440/65R28	625		650/60R34	775		210/95R44 (8.3R44)	725
	340/75R20	500		460/60R28	625		650/65R34	825		230/95R44 (9.5R44)	750
24	360/70R20	500		480/65R28	650		650/75R34	875		270/95R44 (11.2R44)	775
	380/70R20	525		480/70R28	675	30	710/60R34	825		750/70R44	1025
	380/75R20	525		520/60R28	650		710/75R34	925		270/95R46 (11.2R46)	800
	420/65R20	500		540/65R28	675		210/95R36 (8.3R36)	625		300/95R46 (12.4R46)	825
	440/65R20	525		600/60R28	675		230/95R36 (9.5R36)	650		320/90R46	825
	8.3R24	475		600/65R28	700	32	270/95R36 (11.2R36)	675		340/85R46 (13.6R46)	825
	250/85R24 (9.5R24)	500		600/70R28	725		320/85R36 (12.4R36)	700	46	380/90R46	875
	280/85R24 (11.2R24)	525		380/85R30 (14.9R30)	675		340/85R36 (13.6R36)	725		420/80R46	875
	300/70R24	500		420/70R30	675		270/95R38 (11.2R38)	700		480/80R46	925
	320/70R24	525		420/85R30 (16.9R30)	700		320/85R38 (12.4R38)	725		520/85R46 (20.8R46)	975
	320/85R24 (12.4R24)	550		420/90R30	725	34	340/85R38 (13.6R38)	750		620/70R46	975
	340/85R24 (13.6R24)	575		460/85R30 (18.4R30)	725		380/80R38	750		750/75R46	≥ 1075
	360/70R24	550		480/70R30	700		380/95R38	800		900/65R46	≥ 1075
	380/70R24	575		480/75R30	700	36	400/75R38 (15.5R38)	750	48	230/95R48 (9.5R48)	800
	380/85R24 (14.9R24)	600		520/70R30	725		420/85R38 (16.9R38)	800		270/95R48 (11.2R48)	825
25	400/70R24	575		520/85R30	775		460/85R38 (18.4R38)	825		340/85R48 (13.6R48)	875
	420/65R24	550		540/65R30	700		480/70R38	800		320/90R50	875
	420/70R24	600		600/60R30	700	38	520/70R38	825		380/90R50	925
	420/85R24 (16.9R24)	625		600/65R30	725		520/85R38 (20.8R38)	875	50	420/95R50	975
	440/65R24	575		600/70R30	750		540/65R38	800		480/80R50	975
	460/70R24	600		620/70R30	775		600/60R38	800		480/95R50	1025
	480/65R24	600		620/75R30	800		600/65R38	825	52	300/95R52 (12.4R52)	925
	480/70R24	625		650/70R30	800		650/60R38	825		270/95R54 (11.2R54)	925
	500/70R24	625		650/75R30	800	54	580/70R38	875		320/90R54	925
	540/65R24	625		710/55R30	725		620/70R38	875	56	380/90R54	975
	1000/50R25	750		710/60R30	750		650/65R38	875			
							650/75R38	925			

EQUIVALENCE CHART

STAGE 2

Based on the SRI obtained, establish the possible tyre size equivalents.

IMPORTANT :

- In no case does the SRI correspond to a specific tread circumference value. Its use in these tables is purely indicative. Verification measurements must be taken.
- Any changes mean you must calculate the axle ratios, evaluate weight distributions and check that the rim widths and diameters are compatible (see technical pages)

SRI	ÉQUIVALENCES	SRI	ÉQUIVALENCES	SRI	ÉQUIVALENCES	SRI	ÉQUIVALENCES
360	6.50R16	625	210/95R36 // 8.3R36	750	230/95R44 // 9.5R44	875 (1.85m)	320/90R50
	260/70R16		270/95R32 // 11.2R32		270/95R42 // 11.2R42		340/85R48 // 13.6R48
	280/65R16		340/85R28 // 13.6R28		340/85R38 // 13.6R38		380/90R46
390	7.50R16		380/70R28		380/80R38		420/80R46
	250/80R16		420/85R24 // 16.9R24		400/75R38 // 15.5R38		480/80R42 // 18.4R42
	280/70R16		440/65R28		420/85R34 // 16.9R34		520/85R38 // 20.8R38
410	320/65R16		480/60R28		480/70R34		580/70R38
	7.50R18		480/70R24		540/65R34		620/70R38
	280/70R18		500/70R24		600/60R34		650/65R38
425	320/65R18		540/65R24		600/70R30		650/75R34
	7.50R20	650	230/95R36 // 9.5R36		620/75R26 // 23.1R26		680/75R32 // 30.5LR32
	280/70R20		320/85R32 // 12.4R32	775	710/60R30		710/60R38
450	340/65R18		380/85R28 // 14.9R28		750/65R26		800/65R32
	9.5R20		420/70R28		1000/50R25		1000/55R32
	260/80R20		420/75R28		270/95R44 // 11.2R44	925 (1.95m)	1050/50R32
	300/70R20		480/65R28		460/85R34 // 18.4R34		270/95R54 // 11.2R54
	340/65R20		480/70R26		520/85R30		300/95R52 // 12.4R52
475	11.2R20		520/60R28		520/70R34		320/90R54
	280/85R20		540/65R26		520/75R34		380/90R50
	320/70R20	675	270/95R36 // 11.2R36		600/65R34		480/80R46
500	8.3R24		320/85R34 // 12.4R34	800	620/70R30		520/85R42 // 20.8R42
	250/85R24 // 9.5R24		380/85R30 // 14.9R30		650/60R34		620/70R42
	300/70R24		420/70R30		230/95R48 // 9.5R48	975 (2.05m)	650/65R42
525	320/85R20 // 12.4R24		420/85R28 // 16.9R28		270/95R46 // 11.2R46		650/75R38
	340/75R20		480/70R28		300/95R42 // 12.4R42		680/75R38
	360/70R20	700	540/65R28		320/90R42		680/85R32
550	420/65R20		580/70R26		380/95R38		710/60R42
	280/85R24 // 11.2R24		600/60R28		420/85R38 // 16.9R38		710/70R38
	320/70R24		750/50R26		480/70R38		710/75R34
575	380/70R20		230/95R40 // 9.5R40	825 (1.75m)	540/65R38		750/65R38
	380/75R20 // 13.6R20		270/95R38 // 11.2R38		600/60R38	1025 (2.15m)	800/70R32
	14.9LR20	725	320/85R36 // 12.4R36		620/75R30		900/50R42
600	440/65R20		420/85R30 // 16.9R30		650/70R30		900/60R32
	250/85R28 // 9.5R28		480/70R30		650/75R30		380/90R54
	320/85R24 // 12.4R24		480/75R30		270/95R48 // 11.2R48	1075 (2.30m)	420/95R50
625	340/65R28		520/80R26		300/95R46 // 12.4R46		480/80R50
	360/70R24		540/65R30		320/90R46		520/85R46 // 20.8R46
	420/65R24		600/60R30		340/85R46 // 13.6R46		580/85R42
650	210/95R32 // 8.3R32		600/65R28		460/85R38 // 18.4R38		620/70R46
	280/85R28 // 11.2R28	750	210/95R44 // 8.3R44		520/70R38		650/85R38
	320/70R28		320/85R38 // 12.4R38		600/65R38		710/70R42
675	340/85R24 // 13.6R24		340/85R36		620/75R34		800/70R38
	380/70R24		380/85R34		650/75R32 // 24.5R32		900/60R38
	400/70R24		420/90R30		650/65R34	1075 (2.30m)	480/95R50
700	440/65R24		460/85R30 // 18.4R30		650/60R38		650/85R42
	230/95R32 // 9.5R32		600/65R30		710/60R34		710/75R42
	320/85R28 // 12.4R28	775	600/70R28				710/85R38
725	360/70R28		620/70R26				900/60R42
	380/85R24 // 14.9R24		710/55R30				900/65R46
	420/65R28						
	420/70R24						
	460/70R24						
	480/65R24						

TYRES BY SIZE

SEAT	SIZES	TOPKER IF	TOPKER	GRIPKER	FITKER	TRAKER	SUPVIGNE	SUP 8L	SUP G	CROPKER	SUP 3
16	260/70R16				S			S			
16	280/70R16				S			S			
16	7.50R16						S				
18	280/70R18				S						
18	7.50R18						S				
20	280/85R20 (11.2R20)						S				
20	14.9LR20								S		
20	280/70R20				S						
20	300/70R20				S						
20	320/70R20				S						
20	320/85R20					S					
20	340/75R20								S		
20	360/70R20				S						
20	7.50R20						S				
20	9.5R20						S				
22.5	560/60R22.5										
24	280/85R24 (11.2R24)					S	S				
24	320/85R24 (12.4R24)					S					
24	340/85R24 (13.6R24)					S	S				
24	380/85R24 (14.9R24)					S	S				
24	420/85R24 (16.9R24)					S					
24	250/85R24					S					
24	320/70R24				S						
24	360/70R24				S						
24	380/70R24				S						
24	420/70R24				S						
24	440/65R24			S							
24	480/65R24			S							
24	480/70R24				S						
24	540/65R24			S							
24	8.3R24						S				
24	9.5R24						S				
28	280/85R28 (11.2R28)					S	S				
28	320/85R28 (12.4R28)					S	S				
28	340/85R28 (13.6R28)					S	S				
28	380/85R28 (14.9R28)					S	S				
28	420/85R28 (16.9R28)					S					

TYRES BY SIZE

SEAT	SIZES	TOPKER IF	TOPKER	GRIPKER	FITKER	TRAKER	SUP VIGNE	SUP 8L	SUP G	CROPKER	SUP 3
28	250/85R28					S					
28	360/70R28				S						
28	380/70R28				S						
28	420/70R28				S						
28	440/65R28			S							
28	480/65R28			S							
28	480/70R28				S						
28	540/65R28			S							
28	600/65R28	IF									
28	600/70R28	IF	S								
28	9.5R28						S				
30	380/85R30 (14.9R30)					S					
30	420/85R30 (16.9R30)					S			S		
30	460/85R30 (18.4R30)					S					
30	420/70R30				S			S			
30	480/70R30				S						
30	540/65R30			S							
30	600/70R30	IF	S								
32	320/85R32 (12.4R32)					S					
32	210/95R32										S
32	230/95R32									S	
32	270/95R32									S	
34	420/85R34 (16.9R34)					S					
34	460/85R34 (18.4R34)					S					
34	480/70R34				S						
34	520/70R34				S						
34	540/65R34			S							
34	600/65R34			S							
34	650/60R34	IF									
34	650/65R34	IF									
36	320/85R36 (12.4R36)					S					
36	340/85R36 (13.6R36)					S					
36	230/95R36									S	
36	270/95R36									S	
38	340/85R38 (13.6R38)					S					
38	420/85R38 (16.9R38)					S					
38	460/85R38 (18.4R38)					S					

TYRES BY SIZE

SEAT	SIZES	TOPKER IF	TOPKER	GRIPKER	FITKER	TRAKER	SUP VIGNE	SUP 8L	SUP G	CROPKER	SUP 3
38	520/85R38 (20.8R38)					S					
38	270/95R38									S	
38	480/70R38				S						
38	520/70R38				S						
38	540/65R38			S							
38	580/70R38				S						
38	600/65R38			S							
38	650/65R38			S							
38	650/75R38	IF	S								
38	650/85R38	IF	S								
38	710/70R38	IF	S								
38	800/70R38	IF									
40	230/95R40									S	
42	520/85R42 (20.8R42)					S					
42	270/95R42									S	
42	300/95R42									S	
42	620/70R42				S						
42	650/65R42			S							
42	710/70R42	IF	S								
42	710/75R42	IF									
44	210/95R44										S
44	230/95R44									S	
44	270/95R44									S	
46	300/95R46									S	
48	230/95R48									S	
48	270/95R48									S	
52	300/95R52									S	
54	270/95R54									S	

ROLLING CIRCUMFERENCE CHART

Tyre SIZE AND RANGE	CAI	MSPN	Minimum Dual Spacing		Tyre Diameter		Rolling Circumference		RCI	SRI
			mm	inches	mm	inches	mm	inches		
260/70R16 109A8/106B TL FITKER	882055	43436	360	14	768	30	2300	91		370
260/70R16 109A8/106B TL SUP 8L	161811	72087	360	14	776	31	2304	91	29	370
280/70R16 112A8/109B TL FITKER	789353		389	15	799	31	2373	93		390
7.50R16 100A8 TL SUPER VIGNE	460305	57162	300	12	796	31	2388	94		390
280/70R16 112A8/109B TL SUP 8L	161686	72003	389	15	805	32	2404	95	30	390
7.50R18 102A8 TL SUPER VIGNE	574346	64417	300	12	854	34	2553	101		410
280/70R18 114A8/111B TL FITKER	919813	55669	389	15	857	34	2556	101	31	410
7.50R20 104A8 TL SUPER VIGNE	401887		300	12	904	36	2718	107		425
280/70R20 116A8/113B TL FITKER	480724	24145	389	15	904	36	2725	107	32	450
9.5R20 108A8 TL SUPER VIGNE	283935		340	13	938	37	2811	111		450
300/70R20 120A8/117B TL FITKER	523762	73019	405	16	947	37	2814	111		450
300/70R20 119A8/116B TL SUP 8L	161414		405	16	960	38	2852	112		450
320/70R20 123A8/120B TL FITKER	968538		434	17	980	39	2917	115		475
11.2R20 111A8 TL SUPER VIGNE	963152		392	15	983	39	2918	115		475
320/70R20 123A8/120B TL SUP 8L	161740		434	17	990	39	2934	116		475
8.3R24 106A8 TL SUPER VIGNE	257555		304	12	984	39	2951	116		475
9.5R24 107A8 TL SUPER VIGNE	571677		340	13	1027	40	3053	120		500
250/85R24 109A8/106B TL TRAKER	162160		352	14	1042	41	3101	122	35	500
320/85R20 119A8/116B TL TRAKER	161882	56173	434	17	1047	41	3104	122	35	500
360/70R20 129A8/126B TL FITKER	356982	61470	479	19	1047	41	3107	122		500
340/75R20 117A8/114B TT SUP G	160884	43555	462	18	1045	41	3114	123		500
360/70R20 129A8/126B TL SUP 8L	161867	75643	479	19	1062	42	3144	124		500
400/70R20 IND 149A8/149B TL LUGKER	478302		536	21	1062	42	3160	124		525
14.9LR20 119A8/116B TL SUP G	286656		504	20	1092	43	3246	128		525
11.2R24 114A8 TL SUPER VIGNE	162123		392	15	1084	43	3250	128		525
280/85R24 115A8/112B TL TRAKER	161767		389	15	1100	43	3267	129	36	525
320/70R24 116A8/116B TL FITKER	920320	55669	434	17	1103	43	3278	129		525
9.5R28 109A8 TL SUPER VIGNE	188404		340	13	1128	44	3364	132		550
250/85R28 112A8/109B TL TRAKER	162161		352	14	1142	45	3403	134		550
320/85R24 122A8/119B TL TRAKER	161768		434	17	1149	45	3413	134	37	550
360/70R24 122A8/122B TL FITKER	513401		479	19	1153	45	3423	135	37	550
440/65R24 128D TL GRIPKER	397176		580	23	1184	47	3508	138		575
340/85R24 130A8/127B TL TRAKER	760563	83063	462	18	1186	47	3527	139		575
11.2R28 116A8 TL SUPER VIGNE	162127		392	15	1191	47	3545	140	38	575
380/70R24 125A8/125B TL FITKER	761981	54160	507	20	1204	47	3569	141	38	575
280/85R28 118A8/115B TL TRAKER	161885		389	15	1200	47	3571	141		575
13.6R24 121A8 TL SUPER VIGNE	162125	46430	465	18	1188	47	3577	141		575
210/95R32 114A8/114B TL SUP 3	231707		308	12	1212	48	3638	143	38	575

ROLLING CIRCUMFERENCE CHART

Tyre SIZE AND RANGE	CAI	MSPN	Minimum Dual Spacing		Tyre Diameter		Rolling Circumference		RCI	SRI
			mm	inches	mm	inches	mm	inches		
480/65R24 133D TL GRIPKER	987417		626	25	1239	49	3655	144	38	600
14.9R24 126A8 TL SUPER VIGNE	162167		504	20	1241	49	3678	145		600
380/85R24 131A8/128B TL TRAKER	161770		507	20	1252	49	3703	146		600
460/70R24 IND 159A8/159B TL LUGKER	968722		609	24	1240	49	3704	146		600
12.4R28 121A8 TL SUPER VIGNE	162128	57824	429	17	1258	50	3720	146		600
320/85R28 124A8/121B TL TRAKER	161772		434	17	1253	49	3721	146		600
420/70R24 136A8/136B TL FITKER	472806	23575	552	22	1255	49	3727	147	39	600
360/70R28 125A8/125B TL FITKER	761038		479	19	1263	50	3747	148		600
230/95R32 128D/131A8 TL CROPKER	002322		324	13	1256	49	3768	148		600
13.6R28 123A8 TL SUPER VIGNE	162129	87718	465	18	1280	50	3806	150		625
500/70R24 IND 164A8/164B TL LUGKER	265461		654	26	1298	51	3830	151		625
540/65R24 140D TL GRIPKER	357179		711	28	1300	51	3835	151		625
440/65R28 131D TL GRIPKER	501838		580	23	1297	51	3847	151	39	625
380/70R28 127A8/127B TL FITKER	282375		507	20	1308	51	3881	153	39	625
340/85R28 127A8/124B TL TRAKER	161773		462	18	1307	51	3882	153	39	625
420/85R24 142A8/139B TL TRAKER	875390	74884	552	22	1329	52	3949	155		625
480/70R24 138A8/138B TL FITKER	984280	57943	626	25	1338	53	3955	156		625
270/95R32 136D/139A8 TL CROPKER	227326		381	15	1320	52	3957	156		625
480/65R28 136D TL GRIPKER	810788		626	25	1339	53	3958	156		650
230/95R36 130D/133A8 TL CROPKER	239482		324	13	1335	53	4003	158	40	650
14.9R28 128A8 TL SUPER VIGNE	162166	75494	504	20	1348	53	4025	158		650
380/85R28 133A8/130B TL TRAKER	161774	53490	507	20	1360	54	4034	159	40	650
320/85R32 126A8/123B TL TRAKER	161888	49112	434	17	1356	53	4037	159	40	650
420/70R28 133A8/133B TL FITKER	655028	28986	552	22	1366	54	4050	159	40	650
540/65R28 142D TL GRIPKER	212088		711	28	1416	56	4178	164	41	675
380/85R30 135A8/132B TL TRAKER	161886		507	20	1413	56	4188	165	41	675
420/70R30 134A8/131B TL SUP 8L	161033		552	22	1412	56	4202	165	41	675
270/95R36 139D/142A8 TL CROPKER	659295		381	15	1415	56	4207	166	41	675
420/70R30 134A8/131B TL FITKER	661829	17162	552	22	1399	55	4217	166		675
480/70R28 140A8/140B TL FITKER	978324		626	25	1435	56	4244	167	41	675
420/85R28 144A8/141B TL TRAKER	955665	80641	552	22	1435	56	4267	168		675
480/70R28 145A8/145B TL FITKER	897634	95465	626	25	1440	57	4275	168	41	675
230/95R40 132D/135A8 TL CROPKER	265784		324	13	1446	57	4311	170		700
540/65R30 143D TL GRIPKER	024095		711	28	1460	57	4317	170		700
320/85R36 128A8/125B TL TRAKER	161779		434	17	1461	58	4357	172		700
16.9R30 137A8/134B TL SUP G	450712		566	22	1470	58	4362	172	42	700
420/85R30 140A8/137B TL TRAKER	161776	92979	552	22	1474	58	4371	172	42	700

ROLLING CIRCUMFERENCE CHART

Tyre SIZE AND RANGE	CAI	MSPN	Minimum Dual Spacing		Tyre Diameter		Rolling Circumference		RCI	SRI
			mm	inches	mm	inches	mm	inches		
480/70R30 141A8/141B TL FITKER	347735	54027	626	25	1483	58	4400	173	42	700
270/95R38 140D/143A8 TL CROPKER	559899		381	15	1469	58	4410	174	42	700
IF 600/65R28 160D/156E TL TOPKER IF	686028		760	30	1486	59	4417	174	4406	700
600/65R28 154A8/151D TL TOPKER	397382		760	30	1490	59	4420	174	42	700
340/85R36 132A8/129B TL TRAKER	161780		462	18	1503	59	4478	176	42	725
460/85R30 145A8/142B TL TRAKER	161887		597	24	1547	61	4574	180		725
210/95R44 120A8/120B TL SUP 3	169754		308	12	1534	60	4608	181	42	725
600/70R28 157A8/154D TL TOPKER	120140		760	30	1562	61	4637	183		725
230/95R44 134D/137A8 TL CROPKER	625299		324	13	1547	61	4645	183	43	750
IF 600/70R28 164D/160D TL TOPKER IF	774936		760	30	1569	62	4652	183		725
340/85R38 133A8/130B TL TRAKER	161781		462	18	1563	62	4661	184		750
270/95R42 141D/144A8 TL CROPKER	502916		381	15	1563	62	4690	185	43	750
420/85R34 142A8/139B TL TRAKER	161777		552	22	1581	62	4693	185	43	750
540/65R34 145D TL GRIPKER	734934		711	28	1588	63	4695	185	43	750
IF 600/70R30 165D/161E TL TOPKER IF	278892		774	30	1591	63	4709	185	43	750
600/70R30 152A8/149D TL TOPKER	811999		774	30	1590	63	4709	185	43	750
480/70R34 143A8/143B TL FITKER	481973		626	25	1592	63	4745	187	43	750
600/65R34 151D TL GRIPKER	009417		760	30	1639	65	4845	191	44	775
270/95R44 142D/145A8 TL CROPKER	699532		381	15	1618.9	64	4856	191		775
300/95R42 147D/150A8 TL CROPKER	349230		405	16	1627	64	4866	192		775
520/70R34 148A8/148B TL FITKER	289573		676	27	1654	65	4901	193	44	775
460/85R34 147A8/144B TL TRAKER	161778		597	24	1659	65	4916	194		775
420/85R38 144A8/141B TL TRAKER	161782		552	22	1665	66	4947	195	44	800
540/65R38 147D TL GRIPKER	783160		711	28	1677	66	4963	195	44	800
230/95R48 136D/139A8 TL CROPKER	973505		324	13	1659	65	4989	196	44	800
480/70R38 145A8/145B TL FITKER	190745		626	25	1697	67	5045	199	44	800
600/65R38 153D TL GRIPKER	186241		760	30	1748	69	5167	203	45	825
300/95R46 148D/151A8 TL CROPKER	097180		405	16	1734	68	5203	205	45	825
460/85R38 149A8/146B TL TRAKER	161783	67062	597	24	1754	69	5208	205	45	825
270/95R48 144D/147A8 TL CROPKER	199409		381	15	1736	68	5217	205	45	825
520/70R38 150A8/150B TL FITKER	759556		670	26	1765	69	5228	206	45	825
650/65R38 157D TL GRIPKER	005722		825	32	1805	71	5336	210	46	875
520/85R38 155A8/152B TL TRAKER	161784	49040	670	26	1838	72	5452	215	46	875
580/70R38 155A8/155B TL FITKER	857504		743	29	1849	73	5478	216	46	875
300/95R52 151D/154A8 TL CROPKER	747425		405	16	1886	74	5664	223		925
270/95R54 146D/149A8 TL CROPKER	718149		381	15	1887	74	5679	224		925
650/75R38 169A8/166D TL TOPKER	920029		825	32	1925	76	5723	225	47	925

ROLLING CIRCUMFERENCE CHART

Tyre SIZE AND RANGE	CAI	MSPN	Minimum Dual Spacing		Tyre Diameter		Rolling Circumference		RCI	SRI
			mm	inches	mm	inches	mm	inches		
IF 650/75R38 175D/171E TL TOPKER IF	920724		826	33	1932	76	5726	225	47	925
650/65R42 158D TL GRIPKER	001368		825	32	1937	76	5735	226	47	925
520/85R42 157A8/157B TL TRAKER	656000		670	26	1948	77	5776	227	47	925
620/70R42 160A8/160B TL FITKER	101641	83158	801	32	1952	77	5783	228		925
IF 710/70R38 178D/174E TL TOPKER IF	525939		897	35	1955	77	5785	228	47	925
710/70R38 171A8/168D TL TOPKER	602526		910	36	1962	77	5826	229	47	925
IF 650/85R38 179D/175E TL TOPKER IF	690520		821	32	2033	80	6022	237		975
650/85R38 173A8/170D TL TOPKER	368990		825	32	2040	80	6037	238	48	975
IF 800/70R38 179D/175E TL TOPKER IF	873336		1004	40	2052.8	81	6043	238		975
IF 710/70R42 179D/175E TL TOPKER IF	622517		910	36	2082	82	6163	243	48	975
710/70R42 173A8/170D TL TOPKER	281883		910	36	2082	82	6191	244	48	975
IF 710/75R42 181D/178D TL TOPKER IF	902190		910	36	2133	84	6407	252	49	1025
IF 650/60R34 165D/161E TL TOPKER IF	935008		831	33	1644	65	4929	194		775
IF 650/65R34 168D/164E TL TOPKER IF	125859		831	33	1710	67	5122	202		825

LOAD INDEX

LOAD INDEX	KG	LBS	LOAD INDEX	KG	LBS	LOAD INDEX	KG	LBS	LOAD INDEX	KG	LBS
100	800	1 760	151	3 450	7 600	202	15 000	33 100	253	65 000	143 500
101	825	1 820	152	3 550	7 850	203	15 500	34 200	254	67 000	147 500
102	850	1 870	153	3 650	8 050	204	16 000	35 300	255	69 000	152 000
103	875	1 930	154	3 750	8 250	205	16 500	36 400	256	71 000	156 500
104	900	1 980	155	3 875	8 550	206	17 000	37 500	257	73 000	161 000
105	925	2 040	156	4 000	8 800	207	17 500	38 600	258	75 000	165 500
106	950	2 090	157	4 125	9 100	208	18 000	39 700	259	77 500	171 000
107	975	2 150	158	4 250	9 350	209	18 500	40 800	260	80 000	176 500
108	1 000	2 200	159	4 375	9 650	210	19 000	41 900	261	82 500	182 000
109	1 030	2 270	160	4 500	9 900	211	19 500	43 000	262	85 000	187 500
110	1 060	2 340	161	4 625	10 200	212	20 000	44 100	263	87 500	193 000
111	1 090	2 400	162	4 750	10 500	213	20 600	45 400	264	90 000	198 500
112	1 120	2 470	163	4 875	10 700	214	21 200	46 700	265	92 500	204 000
113	1 150	2 540	164	5 000	11 000	215	21 800	48 100	266	95 000	209 500
114	1 180	2 600	165	5 150	11 400	216	22 400	49 400	267	97 500	215 000
115	1 215	2 680	166	5 300	11 700	217	23 000	50 700	268	100 000	220 500
116	1 250	2 760	167	5 450	12 000	218	23 600	52 000	269	103 000	227 000
117	1 285	2 830	168	5 600	12 300	219	24 300	53 600	270	106 000	233 500
118	1 320	2 910	169	5 800	12 800	220	25 000	55 100	271	109 000	240 500
119	1 360	3 000	170	6 000	13 200	221	25 750	56 800	272	112 000	247 000
120	1 400	3 080	171	6 150	13 600	222	26 500	58 400	273	115 000	253 500
121	1 450	3 200	172	6 300	13 900	223	27 250	60 000	274	118 000	260 000
122	1 500	3 300	173	6 500	14 300	224	28 000	61 500	275	121 500	267 000
123	1 550	3 420	174	6 700	14 800	225	29 000	64 000	276	125 000	275 500
124	1 600	3 520	175	6 900	15 200	226	30 000	66 000	277	128 500	283 500
125	1 650	3 640	176	7 100	15 700	227	30 750	68 000	278	132 000	291 000
126	1 700	3 740	177	7 300	16 100	228	31 500	69 500	279	136 000	300 000
127	1 750	3 860	178	7 500	16 500	229	32 500	71 500	280	140 000	308 500
128	1 800	3 960	179	7 750	17 100	230	33 500	74 000	281	145 000	319 500
129	1 850	4 080	180	8 000	17 600	231	34 500	76 000	282	150 000	330 500
130	1 900	4 180	181	8 250	18 200	232	35 500	78 500	283	155 000	341 500
131	1 950	4 300	182	8 500	18 700	233	36 500	80 500	284	160 000	352 500
132	2 000	4 400	183	8 750	19 300	234	37 500	82 500	285	165 000	364 000
133	2 060	4 540	184	9 000	19 800	235	38 750	85 500	286	170 000	375 000
134	2 120	4 680	185	9 250	20 400	236	40 000	88 000	287	175 000	386 000
135	2 180	4 800	186	9 500	20 900	237	41 250	91 000	288	180 000	397 000
136	2 240	4 940	187	9 750	21 500	238	42 500	93 500	289	185 000	408 000
137	2 300	5 080	188	10 000	22 000	239	43 750	96 500	290	190 000	419 000
138	2 360	5 200	189	10 300	22 700	240	45 000	99 000	291	195 000	430 000
139	2 430	5 360	190	10 600	23 400	241	46 250	102 000	292	200 000	441 000
140	2 500	5 520	191	10 900	24 000	242	47 500	104 500	293	206 000	454 000
141	2 575	5 680	192	11 200	24 700	243	48 750	107 500	294	212 000	467 500
142	2 650	5 840	193	11 500	25 400	244	50 000	110 000	295	218 000	480 500
143	2 725	6 000	194	11 800	26 000	245	51 500	113 500	296	224 000	494 000
144	2 800	6 150	195	12 150	26 800	246	53 000	117 000	297	230 000	507 000
145	2 900	6 400	196	12 500	27 600	247	54 500	120 000	298	236 000	520 500
146	3 000	6 600	197	12 850	28 300	248	56 000	123 500	299	243 000	535 500
147	3 075	6 800	198	13 200	29 100	249	58 000	128 000	300	250 000	551 000
148	3 150	6 950	199	13 600	30 000	250	60 000	132 500	301	257 500	567 500
149	3 250	7 150	200	14 000	30 900	251	61 500	135 500	302	265 000	584 000
150	3 350	7 400	201	14 500	32 000	252	63 000	139 000	303	272 500	600 500



KLEBER TOPKER IF

TOPKER switches to IF to boost your traction, improve your comfort and bring better productivity.

✓ TRACTION

- Tyre with lug spacing designed for maximum traction
- Tread profile designed to maximize the contact patch
- IF standard brings up to 15% more traction than standard tyres

✓ LOAD CAPACITY

- IF tyres carry up to 20% more load at the same pressure versus non-IF radial tyre in the same size

✓ COMFORT

- Overlapping lugs to provide a smooth ride on road

SIZES

IF 600/65R28 160D/156E TL

IF 600/70R28 164D/160E TL

IF 600/70R30 165D/161E TL

IF 650/60R34 165D/161E TL **NEW**

IF 650/65R34 168D/164E TL **NEW**

IF 650/75R38 175D/171E TL

IF 650/85R38 179D/175E TL

IF 710/70R38 178D/174E TL

IF 800/70R38 179D/175E TL

IF 710/70R42 179D/175E TL

IF 710/75R42 181D/178D TL **NEW**

KLEBER TOPKER IF

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	IF 600/65R28 160D/156E TL			686028	626	1486	662	4417	DW21B(A)		DW20B (A)		717	405	50
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35
10 km/h			2850	3225	3600	3975	4350	4465	4580	4695	4805	4920	5035	5125	5215
30 km/h			2580	2920	3260	3595	3935	4040	4140	4245	4345	4450	4550	4635	4715
65 km/h			2480	2805	3135	3460	3785	3885	3980	4080	4180	4275	4375	4460	4500
65 km/h Dual	1570	1865	2155	2450	2745	3035	3330	3415	3505	3590	3675	3765	3850	3925	3990
70 km/h			2255	2555	2850	3150	3445	3515	3585	3655	3725	3790	3860	3930	4000

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	IF 600/70R28 164D/160D TL			774936	610	1569	697	4652	DW21B(A)		DW20B (A)		717	448	52
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35
10 km/h			3140	3590	4040	4485	4935	5050	5160	5275	5385	5500	5610	5695	5750
30 km/h			2840	3245	3655	4060	4465	4565	4665	4770	4870	4970	5070	5150	5200
65 km/h			2730	3120	3510	3900	4290	4390	4485	4585	4680	4780	4875	4950	5000
65 km/h Dual	1805	2135	2460	2790	3120	3445	3775	3860	3945	4035	4120	4205	4290	4355	4400
70 km/h			2485	2840	3195	3550	3905	3980	4055	4130	4205	4275	4350	4425	4500

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	IF 600/70R30 165D/161E TL			278892	634	1591	695	4709	DW21B (A)		DW20B (A)		737	468	52
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35
10 km/h			3220	3675	4125	4580	5030	5140	5255	5365	5480	5590	5700	5815	5925
30 km/h			2910	3320	3730	4140	4550	4650	4750	4850	4955	5055	5155	5255	5355
65 km/h			2800	3195	3590	3980	4375	4470	4570	4665	4765	4860	4955	5055	5150
65 km/h Dual	1760	2115	2465	2810	3160	3505	3850	3935	4020	4105	4190	4275	4360	4445	4530
70 km/h			2550	2910	3265	3625	3980	4060	4140	4220	4305	4385	4465	4545	4625

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
34	IF 650/60R34 165D/161E TL NEW			935008	660	1660	744	4929	DW23B (A)		DW24B(A) DW21B(A)		823	499	53	
Bar	0.4	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2	2.2	2.4	
Psi	6	9	12	13	15	16	17	19	20	22	23	26	29	32	35	
10 km/h				3185	3415	3640	3870	4095	4325	4550	4780	5005	5260	5515	5770	5920
30 km/h				2880	3085	3290	3495	3705	3910	4115	4320	4525	4755	4990	5220	5355
65 km/h				2770	2970	3165	3365	3560	3760	3955	4155	4350	4575	4795	5020	5150
65 km/h Dual	1735	2090		2440	2615	2790	2960	3135	3310	3485	3655	3830	4025	4220	4415	4530
70 km/h				2520	2700	2880	3060	3240	3420	3600	3780	3960	4145	4330	4515	4625

* Refer to the notes at the end of the tables of this range

KLEBER TOPKER IF

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
34	IF 650/65R34 168D/164E TL NEW			125859	674	1727	771	5122	DW238(A)		DW248(A)		823	555	53	
Bar	0.4	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2	2.2	2.4	
Psi	6	9	12	13	15	16	17	19	20	22	23	26	29	32	35	
10 km/h				3525	3755	3990	4220	4450	4680	4915	5145	5375	5650	5925	6200	6440
30 km/h				3190	3400	3610	3815	4025	4235	4445	4650	4860	5110	5355	5605	5825
65 km/h				3065	3265	3470	3670	3870	4070	4275	4475	4675	4915	5150	5390	5600
65 km/h Dual	1910	2310		2695	2875	3050	3230	3405	3585	3760	3940	4115	4325	4530	4740	4930
70 km/h				2790	2975	3155	3340	3525	3705	3890	4070	4255	4455	4660	4860	5000

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	IF 650/75R38 175D/171E TL			920724	688	1932	859	5726	DW238 (A)		DW248 (A) DW218 (A)	804	728	58	
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35
10 km/h			4325	4945	5565	6180	6800	6980	7155	7315	7460	7600	7725	7845	7935
30 km/h			3915	4470	5030	5590	6150	6315	6470	6615	6750	6875	6990	7095	7175
65 km/h			3765	4300	4840	5375	5915	6070	6220	6360	6490	6610	6720	6820	6900
65 km/h Dual	2355	2840	3310	3785	4255	4730	5205	5345	5475	5595	5710	5815	5915	6000	6070
70 km/h			3425	3915	4400	4890	5380	5525	5660	5785	5905	6015	6115	6150	6150

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	IF 710/70R38 178D/174E TL			525939	735	1955	864	5785	DW248 (A)		DW238 (A) DW258 (A)		804	825	54	
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4	
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35	
10 km/h				4665	5330	6000	6665	7330	7490	7650	7810	7975	8135	8295	8455	8625
30 km/h				4220	4825	5425	6030	6630	6775	6925	7070	7215	7360	7510	7655	7800
65 km/h				4055	4635	5215	5795	6375	6515	6655	6795	6930	7070	7210	7350	7500
65 km/h Dual	2560	3060		3570	4080	4590	5100	5610	5735	5855	5980	6100	6225	6345	6470	6600
70 km/h				3690	4220	4745	5275	5800	5925	6055	6180	6310	6435	6565	6690	6700

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	IF 650/85R38 179D/175E TL			690520	696	2033	902	6022	DW238 (A)		DW208 (A) MW238 (A)		804	857	61	
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4	
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35	
10 km/h				4890	5580	6125	6670	7220	7490	7765	8035	8310	8460	8615	8765	8915
30 km/h				4420	5045	5540	6035	6525	6775	7020	7270	7515	7650	7790	7925	8060
65 km/h				4250	4850	5325	5800	6275	6515	6750	6990	7225	7355	7490	7620	7750
65 km/h Dual	2640	3190		3740	4270	4685	5105	5520	5730	5940	6150	6360	6475	6590	6705	6820
70 km/h				4000	4500	5050	5600	6150	6240	6325	6415	6500	6600	6700	6800	6900

* Refer to the notes at the end of the tables of this range

KLEBER TOPKER IF

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	IF 800/70R38 179D/175E TL	873336	785.2	2053	892	6043	DW25B (A)	MW25B (A) DW27B (A)	804	1073	58
Bar	0.4 0.6 0.8	1	1.2	1.4	1.6						
Psi	6 9 12	15	17	20	23						
10 km/h		5605	6440	7245	8080	8915					
30 km/h		5070	5810	6550	7305	8060					
65 km/h		4875	5590	6300	7025	7750					
65 km/h Dual	3035 3665	4290	4920	5545	6185	6820					
70 km/h		4340	4985	5605	6255	6900					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
42	IF 710/70R42 179D/175E TL			622517	716	2082	926	6163	DW25B (A)		DW23B (A) MW25B (A)		802	872	59	
Bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.7	1.8	1.9	2	2.1	2.2	2.3	2.4	
Psi	6	9	12	15	17	20	23	25	26	28	29	30	32	33	35	
10 km/h				4890	5560	6110	6660	7215	7490	7765	8040	8315	8465	8615	8765	8915
30 km/h				4420	5045	5540	6035	6525	6775	7020	7270	7515	7650	7790	7925	8060
65 km/h				4250	4850	5325	5800	6275	6515	6750	6990	7225	7355	7490	7620	7750
65 km/h Dual	2640	3190		3740	4270	4685	5105	5520	5730	5940	6150	6360	6475	6590	6705	6820
70 km/h				3870	4415	4860	5305	5755	5975	6200	6420	6645	6710	6775	6835	6900

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	IF 710/75R42 181D/178D TL NEW				902190	730	2161	957	6407	DW25B(A)		DW23B(A) DW24B(A)		802	949	57
Bar	0.4	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2	2.2	2.4	
Psi	6	9	12	13	15	16	17	19	20	22	23	26	29	32	35	
10 km/h				5175	5560	5940	6325	6710	7090	7475	7765	8050	8625	9030	9260	9490
30 km/h				4680	5020	5355	5695	6030	6370	6710	7045	7385	7685	7985	8280	8580
65 km/h				4500	4825	5150	5475	5800	6125	6450	6775	7100	7390	7675	7965	8250
65 km/h Dual	2860	3410		3960	4245	4535	4820	5105	5390	5680	5965	6250	6505	6755	7010	7260
70 km/h				4095	4390	4690	4985	5280	5575	5870	6160	6455	6750	7045	7275	7500

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER TOPKER

Excellent price-performance ratio corresponding to original equipment sizes.

✓ TRACTION

- Specific lug design for maximum traction.

✓ SELF-CLEANING

- A new inter-lug design to assist self-cleaning.

✓ TYRE LIFE

- Stable tread design to prevent irregular wear.

SIZES

600/65R28 154A8/151D TL

600/70R28 157A8/154D TL

600/70R30 152A8/149D TL

650/75R38 169A8/166D TL

710/70R38 171A8/168D TL

650/85R38 173A8/170D TL

710/70R42 173A8/170D TL

KLEBER TOPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)		Tread depth (mm)
28	600/65R28 154A8/151D TL			397382	607	1490	745	4420	DW20B (A)		DW18L W18L		717	405		50
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.6	2.8	
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	38	41	
10 km/h	2250	2680	3115	3545	3760	3975	4125	4275	4425	4575	4825	5025	5225	5425	5625	
30 km/h	1875	2195	2515	2835	2970	3105	3235	3370	3450	3530	3695	3855	4015			
40 km/h			2360	2650	2775	2900	3025	3150	3225	3300	3450	3600	3750			
50 km/h				2410	2525	2640	2750	2865	2935	3005	3140	3280	3415			
65 km/h				2410	2525	2640	2750	2865	2935	3005	3140	3280	3415			

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	600/70R28 157A8/154D TL				120140	618	1562	700	4637	DW20B (A)		DW18L		717	448	51
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.6	2.8	
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	38	41	
10 km/h	2475	2945	3415	3880	4115	4350	4545	4740	4935	5130	5420	5615	5805	6000	6190	
30 km/h	2085	2425	2765	3105	3280	3455	3625	3800	3875	3955	4110	4260	4415			
40 km/h			2575	2900	3065	3225	3390	3550	3620	3695	3840	3980	4125			
50 km/h				2640	2790	2935	3085	3230	3295	3360	3495	3625	3755			
65 km/h				2640	2790	2935	3085	3230	3295	3360	3495	3625	3755			

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	600/70R30 152A8/149D TL			811999	612	1590	705	4709	DW20B (A)		DW18L W18L	737	456	51
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2			
Psi	9	12	15	17	19	20	22	23	25	26	29			
10 km/h	3000	3390	3780	4140	4310	4475	4640	4810	4975	5140	5475			
30 km/h	2140	2525	2835	3190	3370	3545	3725	3900						
40 km/h		2360	2650	2950	3100	3250	3400	3550						
50 km/h			2360	2655	2805	2955	3100	3250						
65 km/h			2360	2655	2805	2955	3100	3250						

* Refer to the notes at the end of the tables of this range

KLEBER TOPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	650/75R38 169A8/166D TL			920029	670	1925	867	5723	DW23B (A)				804	723	58
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.6	2.8
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	38	41
10 km/h	3360	4020	4680	5340	5670	6000	6265	6525	6790	7050	7470	7775	8085	8390	8700
30 km/h	2915	3370	3825	4280	4515	4750	4980	5215	5340	5465	5710	5960	6205		
40 km/h			3550	4000	4220	4440	4655	4875	4990	5105	5340	5570	5800		
50 km/h				3640	3840	4040	4235	4435	4540	4645	4860	5070	5280		
65 km/h				3640	3840	4040	4235	4435	4540	4645	4860	5070	5280		

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	710/70R38 171A8/168D TL				602526	713	1962	880	5826	DW23B (A)	MW23B (A) DW25B (A) MW25B (A)	804	815	54	
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.8	
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	41	
10 km/h	4350	4935	5520	6110	6410	6710	7010	7310	7470	7630	7950	8270	8585	8905	9225
30 km/h	3100	3625	4145	4680	4930	5175	5425	5670	5785	5900	6125	6355	6580		
40 km/h			3875	4375	4605	4840	5070	5300	5405	5515	5725	5940	6150		
50 km/h				4000	4220	4440	4655	4875	4965	5055	5240	5420	5600		
65 km/h				4000	4220	4440	4655	4875	4965	5055	5240	5420	5600		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	650/85R38 173A8/170D TL			368990	702	2040	913	6037	DW23B (A)		DW20B (A) MW23B (A)		804	857	61
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.6	2.8
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	38	41
10 km/h	4500	5100	5700	6300	6600	6900	7200	7500	7690	7875	8250	8625	9000	9375	9750
30 km/h	3250	3800	4350	4900	5175	5450	5725	6000	6115	6225	6450	6675	6900		
40 km/h			4000	4485	4725	4965	5210	5450	5580	5715	5975	6240	6500		
50 km/h				4485	4725	4970	5210	5450	5580	5715	5975	6240	6500		
65 km/h				4140	4365	4585	4810	5030	5150	5275	5515	5760	6000		

* Refer to the notes at the end of the tables of this range

KLEBER TOPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	710/70R42 173A8/170D TL			281883	716	2082	939	6191	DW23B (A)		MW23B (A) DW25B (A) MW25B (A)		802	872	59
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2	2.2	2.4	2.6	2.8
Psi	9	12	15	17	19	20	22	23	25	26	29	32	35	38	41
10 km/h	4500	5100	5700	6300	6600	6900	7200	7500	7690	7875	8250	8625	9000	9375	9750
30 km/h	3210	3745	4280	4815	5110	5410	5705	6000	6120	6240	6480	6715	6955		
40 km/h			4000	4500	4775	5050	5325	5600	5715	5825	6050	6275	6500		
50 km/h				4125	4380	4640	4895	5150	5255	5365	5575	5790	6000		
65 km/h				4125	4380	4640	4895	5150	5255	5365	5575	5790	6000		

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER GRIPKER

A multi-purpose tyre
with great traction
that protects the soil.

✓ TRACTION

- Deep tread depth and exclusive tread pattern ensure great traction and excellent self-cleaning properties.

✓ RIDE COMFORT

- Flexible casing and specific tread pattern ensure high comfort on the road, up to 65 km/h.

✓ SOIL PROTECTION

- Rounded lugs help protect the plant roots.

SIZES

440/65R24 128D TL

480/65R24 133D TL

540/65R24 140D TL

440/65R28 131D TL

480/65R28 136D TL

540/65R28 142D TL

540/65R30 143D TL

540/65R34 145D TL

600/65R34 151D TL

540/65R38 147D TL

600/65R38 153D TL

650/65R38 157D TL

650/65R42 158D TL

KLEBER GRIPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
24	440/65R24 128D TL			397176	440	1184	525	3508	DW14L	DW13 W13 W14L DW15L W15L	703	178	42		
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	1380	1495	1605	1720	1835	1945	2060	2145	2225	2310	2395	2475	2560	2640	2725
30 km/h	1120	1230	1340	1450	1560	1670	1780	1855	1925	2000	2070				
40 km/h			1285	1390	1495	1595	1700	1770	1835	1905	1970				
50 km/h					1430	1530	1630	1695	1760	1825	1890				
65 km/h					1360	1455	1550	1615	1675	1740	1800				

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	480/65R24 133D TL				987417	483	1239	540	3655	DW15L		DW14L W14L W15L	710	218	44
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	1615	1740	1865	1990	2110	2235	2360	2460	2560	2655	2755	2855	2955	3050	3150
30 km/h	1290	1410	1530	1650	1770	1890	2010	2100	2190	2280	2370				
40 km/h			1455	1570	1690	1805	1920	2005	2090	2175	2260				
50 km/h					1620	1730	1840	1920	2000	2080	2160				
65 km/h					1540	1645	1750	1830	1905	1985	2060				

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	540/65R24 140D TL				357179	532	1300	566	3835	DW16L		W16L DW18L W18L	710	287	46
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	1900	2050	2200	2350	2500	2650	2800	2920	3040	3155	3275	3395	3515	3630	3750
30 km/h	1530	1680	1835	1985	2135	2290	2440	2550	2660	2770	2880				
40 km/h			1745	1890	2035	2175	2320	2425	2530	2635	2740				
50 km/h					1950	2090	2230	2330	2430	2530	2630				
65 km/h					1855	1990	2120	2215	2310	2405	2500				

* Refer to the notes at the end of the tables of this range

KLEBER GRIPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
28	440/65R28 131D TL			501838	431	1297	578	3847	DW14L	W13 W14L DW15L W15L		821	198	42	
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	1520	1630	1740	1850	1960	2070	2180	2270	2360	2450	2540	2630	2720	2810	2900
30 km/h	1190	1310	1425	1545	1665	1780	1900	1985	2070	2155	2240				
40 km/h			1355	1470	1585	1695	1810	1895	1975	2060	2140				
50 km/h					1515	1625	1730	1810	1890	1970	2050				
65 km/h					1445	1550	1650	1725	1800	1875	1950				

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	480/65R28 136D TL				810788	480	1339	588	3958	DW15L		DW14L W14L W15L	822	249	44
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	1710	1840	1975	2105	2235	2370	2500	2605	2715	2820	2925	3030	3140	3245	3350
30 km/h	1370	1505	1645	1780	1915	2055	2190	2290	2385	2485	2580				
40 km/h			1560	1690	1820	1950	2080	2175	2265	2360	2450				
50 km/h					1750	1875	2000	2090	2175	2265	2350				
65 km/h					1665	1785	1900	1985	2070	2155	2240				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
28	540/65R28 142D TL			212088	535	1416	617	4178	DW16L		W16L DW18L W18L	822	318	48	
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2070	2225	2380	2535	2690	2845	3000	3125	3250	3375	3500	3625	3750	3875	4000
30 km/h	1645	1800	1955	2115	2270	2425	2580	2700	2815	2935	3050				
40 km/h			1855	2005	2155	2300	2450	2565	2675	2790	2900				
50 km/h					2065	2210	2350	2460	2565	2675	2780				
65 km/h					1970	2105	2240	2345	2445	2550	2650				

* Refer to the notes at the end of the tables of this range

KLEBER GRIPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	540/65R30 143D TL			024095	527	1460	642	4317	DW16L		W16L DW18L W18L		754	333	46
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2130	2290	2445	2605	2760	2920	3075	3205	3340	3470	3600	3730	3865	3995	4125
30 km/h	1690	1850	2010	2170	2330	2490	2650	2770	2890	3010	3130				
40 km/h			1915	2065	2220	2370	2520	2635	2750	2865	2980				
50 km/h					2130	2275	2420	2530	2640	2750	2860				
65 km/h					2025	2165	2300	2405	2515	2620	2725				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	540/65R34 145D TL			734934	527	1588	698	4695	DW16L		W16L DW18L W18L		704	364	47
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2240	2410	2575	2745	2915	3080	3250	3390	3530	3670	3815	3955	4095	4235	4375
30 km/h	1805	1985	2165	2345	2520	2700	2880	2995	3110	3225	3340				
40 km/h			2060	2230	2400	2570	2740	2850	2960	3070	3180				
50 km/h					2300	2465	2630	2735	2840	2945	3050				
65 km/h					2190	2345	2500	2600	2700	2800	2900				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	600/65R34 151D TL			009417	603	1639	721	4845	DW20B (A)		DW18L W18L		823	464	51
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2660	2865	3065	3270	3470	3675	3875	4035	4195	4355	4515	4670	4830	4990	5150
30 km/h	2130	2330	2535	2735	2935	3140	3340	3500	3655	3815	3970				
40 km/h			2415	2605	2800	2990	3180	3330	3480	3630	3780				
50 km/h					2685	2870	3050	3195	3335	3480	3620				
65 km/h					2550	2725	2900	3040	3175	3315	3450				

* Refer to the notes at the end of the tables of this range

KLEBER GRIPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	540/65R38 147D TL			783160	517	1677	741	4963	DW16L		W16L DW18L W18L		824	394	46
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2375	2555	2735	2915	3090	3270	3450	3595	3745	3890	4040	4185	4330	4480	4625
30 km/h	1910	2085	2260	2435	2610	2785	2960	3105	3250	3395	3540				
40 km/h			2155	2320	2490	2655	2820	2960	3095	3235	3370				
50 km/h					2385	2545	2700	2835	2965	3100	3230				
65 km/h					2270	2425	2575	2700	2825	2950	3075				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	600/65R38 153D TL			186241	591	1748	768	5167	DW20B (A)		DW18L W18L		825	500	52
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	2820	3040	3255	3475	3690	3910	4125	4290	4455	4620	4790	4955	5120	5285	5450
30 km/h	2250	2465	2680	2895	3110	3325	3540	3705	3870	4035	4200				
40 km/h			2555	2760	2965	3165	3370	3530	3685	3845	4000				
50 km/h					2835	3035	3230	3380	3530	3680	3830				
65 km/h					2700	2890	3075	3220	3365	3505	3650				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	650/65R38 157D TL			005722	651	1805	794	5336	DW20B (A)				825	602	55
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h	3185	3425	3665	3905	4145	4385	4625	4815	5005	5195	5390	5580	5770	5960	6150
30 km/h	2520	2760	3005	3245	3485	3730	3970	4165	4355	4550	4740				
40 km/h			2855	3085	3320	3550	3780	3965	4150	4335	4520				
50 km/h					3180	3400	3620	3800	3975	4155	4330				
65 km/h					3030	3240	3450	3620	3790	3955	4125				

* Refer to the notes at the end of the tables of this range

KLEBER GRIPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	650/65R42 158D TL				001368	636	1937	858	5735	DW20B (A)				802	647	56
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2	
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	29	
10 km/h	3280	3525	3770	4015	4260	4505	4750	4955	5155	5360	5565	5765	5970	6170	6375	
30 km/h	2650	2910	3165	3425	3685	3940	4200	4375	4545	4720	4890					
40 km/h			3015	3260	3510	3755	4000	4165	4325	4490	4650					
50 km/h					3360	3595	3830	3990	4145	4305	4460					
65 km/h					3205	3430	3650	3800	3950	4100	4250					

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50%

**10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER FITKER

Increase your load capacity
with KLEBER Fitker

✓ RIDE COMFORT

- Thanks to a Flexible casing

✓ VERSATILITY

- Wider than a standard tyre with a greater volume of air.

SIZES

260/70R16 109A8/106B TL
280/70R16 112A8/109B TL
280/70R18 114A8/111B TL
280/70R20 116A8/113B TL
300/70R20 120A8/117B TL
320/70R20 123A8/120B TL
360/70R20 129A8/126B TL
320/70R24 116A8/116B TL
360/70R24 122A8/122B TL

380/70R24 125A8/125B TL
420/70R24 136A8/136B TL
480/70R24 138A8/138B TL
360/70R28 125A8/125B TL
380/70R28 127A8/127B TL
420/70R28 133A8/133B TL
480/70R28 145A8/145B TL
420/70R30 134A8/131B TL
480/70R30 141A8/141B TL

480/70R34 143A8/143B TL
520/70R34 148A8/148B TL
480/70R38 145A8/145B TL
520/70R38 150A8/150B TL
580/70R38 155A8/155B TL
620/70R42 160A8/160B TL

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
16	260/70R16 109A8/106B TL			882055	256	768	346	2300	W9		W8		184	44	29
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	520	615	660	705	755	800	850	895	940	990	1080	1220	1365	1505	1550
30 km/h	440	515	550	585	625	660	695	735	770	805	880	990	1100		
40 km/h	410	480	515	550	580	615	650	685	720	755	825	925	1030		
50 km/h		445	475	510	540	570	605	635	665	700	760	855	950		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
16	280/70R16 112A8/109B TL			789353	263	799	358	2373	W9		W10L W8L W8	184	50	29	
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	580	680	730	780	830	880	930	980	1030	1080	1180	1330	1480	1630	1680
30 km/h	495	575	615	650	690	730	770	810	850	885	965	1085	1200		
40 km/h	460	535	570	605	645	680	715	755	790	825	900	1010	1120		
50 km/h		495	530	560	595	630	660	695	730	765	830	930	1030		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
18	280/70R18 114A8/111B TL			919813	276	857	386	2556	W9		W10		438	56	29
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	620	725	775	830	880	935	985	1040	1090	1145	1245	1405	1560	1720	1770
30 km/h	520	600	645	685	725	765	810	850	890	930	1015	1135	1260		
40 km/h	490	565	605	645	680	720	760	795	835	875	950	1065	1180		
50 km/h		510	545	580	615	650	680	715	750	785	855	955	1060		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	280/70R20 116A8/113B TL			480724	268	904	408	2725	W9		W8 W10		533	61	29
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	640	800	880	960	1035	1115	1195	1275	1340	1400	1525	1655	1750	1850	1880
30 km/h	545	640	690	735	785	830	875	920	965	1010	1095	1215	1340		
40 km/h	515	600	645	690	730	775	820	865	905	950	1025	1140	1250		
50 km/h		545	585	625	665	705	745	785	825	865	935	1035	1140		

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	300/70R20 120A8/117B TL			523762	292	947	426	2814	W9		W8 W10		542	71	31
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	710	830	890	950	1010	1075	1135	1195	1255	1315	1435	1615	1800	1980	2040
30 km/h	605	700	750	795	845	890	940	985	1035	1080	1175	1320	1460		
40 km/h	580	665	710	755	795	840	885	925	970	1015	1100	1230	1360		
50 km/h		610	650	690	730	770	810	850	890	930	1010	1130	1250		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	320/70R20 123A8/120B TL			968538	320	980	442	2917	W10		W9 W11		542	83	33
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	795	935	1005	1075	1145	1210	1280	1350	1420	1490	1630	1840	2045	2255	2325
30 km/h	675	785	840	895	950	1005	1060	1115	1170	1220	1330	1495	1660		
40 km/h	630	730	785	835	885	935	990	1040	1090	1140	1245	1395	1550		
50 km/h		665	710	755	805	850	895	940	985	1035	1125	1260	1400		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
20	360/70R20 129A8/126B TL			356982	366	1047	464	3107	W11	W9 W10 W12	664	108	31		
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	950	1115	1200	1285	1365	1450	1530	1615	1700	1780	1950	2200	2445	2695	2780
30 km/h	800	930	1000	1065	1130	1195	1260	1325	1390	1455	1585	1785	1980		
40 km/h	750	870	935	995	1055	1115	1180	1240	1300	1360	1485	1665	1850		
50 km/h		800	855	915	970	1025	1080	1140	1195	1250	1365	1530	1700		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	320/70R24 116A8/116B TL			920320	332	1103	496	3278	W10		W9 W11		692	105	37
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		1170	1225	1280	1330	1385	1440	1495	1545	1600	1710	1880			
30 km/h	890	980	1025	1070	1115	1160	1205	1250	1295	1340					
40 km/h	830	915	955	1000	1040	1080	1125	1165	1210	1250					
50 km/h		915	955	1000	1040	1085	1125	1165	1210	1250					

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	360/70R24 122A8/122B TL			513401	371	1153	517	3423	W11		W10 W12		692	137	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		1410	1475	1540	1605	1670	1735	1800	1865	1930	2060	2250			
30 km/h	1070	1180	1230	1285	1340	1395	1450	1500	1555	1610					
40 km/h	990	1090	1145	1195	1245	1295	1345	1400	1450	1500					
50 km/h		1090	1140	1195	1245	1295	1345	1400	1450	1500					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	380/70R24 125A8/125B TL				761981	390	1204	536	3569	W12		W11 W13	700	161	41
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		1550	1620	1695	1765	1835	1905	1980	2050	2120	2265	2480			
30 km/h	1170	1290	1350	1410	1470	1530	1590	1650	1710	1770					
40 km/h	1090	1200	1260	1315	1370	1425	1480	1540	1595	1650					
50 km/h	1200	1255	1315	1370	1425	1480	1540	1595	1650						

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	420/70R24 136A8/136B TL				472806	437	1255	563	3727	W13		W12 DW14L W14L	703	203	43
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	1315	1570	1695	1820	1945	2075	2200	2325	2430	2535	2745	2965	3135	3305	3360
30 km/h	1120	1300	1390	1480	1570	1660	1755	1850	1940	2035	2125	2265	2400		
40 km/h	1030	1205	1290	1375	1465	1550	1640	1725	1815	1900	1985	2115	2240		
50 km/h		1205	1290	1380	1465	1550	1640	1725	1815	1900	1985	2115	2240		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	480/70R24 138A8/138B TL			984280	494	1338	589	3955	DW15L		DW14L W14L W15L DW16L W16L	710	276	46
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h		2210	2315	2415	2520	2620	2725	2825	2930	3030	3235	3540		
30 km/h	1680	1850	1935	2020	2105	2190	2275	2360	2445	2530				
40 km/h	1560	1720	1800	1880	1960	2040	2120	2200	2280	2360				
50 km/h	1720	1800	1880	1960	2040	2120	2200	2280	2360					

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	360/70R28 125A8/125B TL			761038	368	1263	565	3747	DW11		W10 W12		726	153	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		1550	1620	1695	1765	1835	1905	1980	2050	2120	2265	2480			
30 km/h	1170	1290	1350	1410	1470	1530	1590	1650	1710	1770					
40 km/h	1090	1200	1260	1315	1370	1425	1480	1540	1595	1650					
50 km/h		1200	1255	1315	1370	1425	1480	1540	1595	1650					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	380/70R28 127A8/127B TL				282375	392	1308	594	3881	W12		W11 W13	732	179	41
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		1640	1715	1795	1870	1945	2020	2100	2175	2250	2400	2630			
30 km/h	1250	1375	1435	1500	1560	1620	1685	1745	1810	1870					
40 km/h	1160	1280	1335	1395	1455	1515	1575	1630	1690	1750					
50 km/h		1280	1340	1400	1455	1515	1575	1635	1690	1750					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	420/70R28 133A8/133B TL			655028	439	1366	608	4050	W13		W12 DW14L W14L	821	231	42
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h		1930	2020	2110	2195	2285	2375	2465	2550	2640	2820	3090		
30 km/h	1470	1615	1690	1760	1835	1910	1980	2055	2125	2200				
40 km/h	1360	1500	1570	1640	1710	1780	1850	1920	1990	2060				
50 km/h		1500	1570	1640	1710	1780	1850	1920	1990	2060				

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	480/70R28 145A8/145B TL				897634	486	1440	645	4275	DW15L	DW14L W14L W15L DW16L W16L		822	302	46
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	1725	2065	2235	2410	2580	2750	2920	3090	3220	3355	3620	3885	4085	4285	4350
30 km/h	1475	1715	1835	1960	2080	2200	2320	2440	2560	2680	2785	2945	3100		
40 km/h	1360	1595	1710	1825	1945	2060	2170	2280	2390	2500	2600	2750	2900		
50 km/h		1595	1710	1830	1945	2060	2170	2280	2390	2500	2600	2750	2900		

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	420/70R30 134A8/131B TL			661829	410	1399	628	4217	W13		W12 DW14L W14	734	205	41
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h	1460	1725	1825	1920	2055	2185	2280	2375	2500	2625	2835	3180		
30 km/h	1230	1455	1560	1660	1770	1875	1980	2085	2180	2270				
40 km/h	1150	1360	1455	1550	1650	1750	1850	1950	2035	2120				
50 km/h		1250	1340	1425	1515	1600	1690	1775	1865	1950				

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	480/70R30 141A8/141B TL				347735	495	1483	662	4400	DW15L	DW14L W14L W15L DW16L W16L	754	317	48
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h		2410	2525	2635	2750	2860	2975	3085	3200	3310	3530	3860		
30 km/h	1830	2015	2110	2200	2295	2390	2480	2575	2665	2760				
40 km/h	1700	1875	1965	2050	2140	2230	2315	2405	2490	2580				
50 km/h		1875	1965	2050	2140	2230	2315	2405	2490	2580				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	480/70R34 143A8/143B TL			481973	497	1592	707	4745	DW15L		DW14L W14L W15L DW16L W16L		704	345	47
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		2550	2670	2790	2905	3025	3145	3265	3380	3500	3735	4090			
30 km/h	1940	2135	2235	2330	2430	2530	2625	2725	2820	2920					
40 km/h	1800	1985	2080	2170	2265	2360	2450	2545	2635	2730					
50 km/h		1985	2080	2170	2265	2360	2450	2545	2635	2730					

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	520/70R34 148A8/148B TL			289573	535	1654	734	4901	DW16L		DW15L W15L W16L DW18L W18L	823	422	51
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h		2950	3085	3225	3360	3495	3630	3770	3905	4040	4315	4730		
30 km/h	2240	2465	2580	2690	2805	2920	3030	3145	3255	3370				
40 km/h	2080	2295	2400	2510	2615	2720	2830	2935	3045	3150				
50 km/h		2295	2400	2510	2615	2725	2830	2935	3045	3150				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	480/70R38 145A8/145B TL			190745	492	1697	765	5045	DW15L		DW14L W14L W15L DW16L W16L		786	377	48
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h		2720	2845	2970	3095	3220	3345	3470	3595	3720	3970	4350			
30 km/h	2060	2270	2370	2475	2580	2685	2790	2890	2995	3100					
40 km/h	1910	2110	2205	2305	2405	2505	2605	2700	2800	2900					
50 km/h		2110	2210	2310	2405	2505	2605	2705	2800	2900					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	520/70R38 150A8/150B TL				759556	536	1765	783	5228	DW16L	DW15L W15L W16L DW18L W18L	824	464	51
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h		3140	3285	3430	3575	3720	3865	4010	4155	4300	4590	5030		
30 km/h	2380	2620	2740	2860	2980	3100	3220	3340	3460	3580				
40 km/h	2210	2440	2550	2665	2780	2895	3010	3120	3235	3350				
50 km/h	2440	2555	2670	2780	2895	3010	3125	3235	3350					

* Refer to the notes at the end of the tables of this range

KLEBER FITKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	580/70R38 155A8/155B TL			857504	606	1849	821	5478	DW18L	W18L	825	590	56
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h		3630	3800	3965	4135	4300	4470	4635	4805	4970	5305	5810	
30 km/h	2760	3040	3175	3315	3455	3595	3735	3870	4010	4150			
40 km/h	2560	2825	2955	3090	3220	3350	3485	3615	3750	3880			
50 km/h		2820	2955	3085	3220	3350	3485	3615	3750	3880			

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	620/70R42 160A8/160B TL			101641	631	1952	866	5783	DW20B (A)		DW18L		802	658	56
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	3640	4055	4260	4470	4675	4885	5090	5300	5505	5715	6130	6750			
30 km/h	3180	3510	3670	3835	4000	4165	4330	4490	4655	4820					
40 km/h	2970	3275	3430	3580	3735	3890	4040	4195	4345	4500					
50 km/h		3275	3430	3580	3735	3890	4040	4195	4345	4500					

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).

TRACTORS - LOW & MEDIUM POWER

STANDARD SERIES - UP TO 170 HP TRACTORS



KLEBER TRAKER

Offers longevity and reliability
from 20" to 42".

✓ RELIABILITY AND LONGEVITY

- Durable casing and high-quality rubber able to work hard.

✓ TRACTION

- A flat tread pattern to maximize contact with the ground.
- Designed for traction work.

SIZES

320/85R20 119A8/116B TL

250/85R24 109A8/106B TL

280/85R24 115A8/112B TL

320/85R24 122A8/119B TL

340/85R24 130A8/127B TL

380/85R24 131A8/128B TL

420/85R24 142A8/139B TL

250/85R28 112A8/109B TL

280/85R28 118A8/115B TL

320/85R28 124A8/121B TL

340/85R28 127A8/124B TL

380/85R28 133A8/130B TL

420/85R28 144A8/141B TL

380/85R30 135A8/132B TL

420/85R30 140A8/137B TL

460/85R30 145A8/142B TL

320/85R32 126A8/123B TL

420/85R34 142A8/139B TL

460/85R34 147A8/144B TL

320/85R36 128A8/125B TL

340/85R36 132A8/129B TL

340/85R38 133A8/130B TL

420/85R38 144A8/141B TL

460/85R38 149A8/146B TL

520/85R38 155A8/152B TL

520/85R42 157A8/157B TL

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	320/85R20 119A8/116B TL			161882	332	1047	466	3104	W11		W8 W10		444	105	38
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1160	1275	1335	1395	1455	1510	1570	1630	1690	1745	1865	2040			
30 km/h	950	1050	1105	1155	1205	1255	1305	1360	1410	1460					
40 km/h		980	1030	1075	1125	1170	1220	1265	1315	1360					
50 km/h				980	1025	1070	1115	1160	1205	1250					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	250/85R24 109A8/106B TL			162160	248	1042	472	3101	W8		W7		686	68	37
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	880	970	1015	1060	1105	1150	1195	1235	1280	1325	1415	1550			
30 km/h	720	795	835	870	910	950	985	1025	1060	1100					
40 km/h		740	775	815	850	885	920	960	995	1030					
50 km/h				740	775	810	845	880	915	950					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	280/85R24 115A8/112B TL			161767	288	1100	493	3267	W10		W9		692	88	37
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1040	1145	1195	1250	1300	1350	1405	1455	1510	1560	1665	1820			
30 km/h	850	940	985	1030	1075	1120	1165	1210	1255	1300					
40 km/h		870	915	960	1000	1045	1090	1135	1175	1220					
50 km/h				870	910	955	995	1035	1080	1120					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	320/85R24 122A8/119B TL			161768	324	1149	516	3413	W11		W10		692	121	42
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1280	1410	1475	1540	1605	1670	1735	1795	1860	1925	2055	2250			
30 km/h	1040	1155	1210	1270	1325	1380	1440	1495	1555	1610					
40 km/h		1080	1135	1185	1240	1290	1345	1395	1450	1500					
50 km/h				1060	1110	1160	1210	1260	1310	1360					

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	340/85R24 130A8/127B TL			760563	350	1186	535	3527	W12		W11		700	143	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1410	1555	1625	1695	1765	1840	1910	1980	2050	2125	2265	2480	2620	2710	2850
30 km/h	1150	1275	1335	1400	1460	1520	1585	1645	1710	1770	1835	1935	2035		
40 km/h		1190	1250	1305	1365	1420	1480	1535	1595	1650	1715	1805	1900		
50 km/h				1170	1225	1280	1335	1390	1445	1500	1560	1645	1730		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	380/85R24 131A8/128B TL			161770	390	1252	551	3703	W13		W11 W12		703	180	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1670	1840	1920	2005	2090	2175	2260	2340	2425	2510	2680	2930			
30 km/h	1360	1505	1580	1650	1725	1800	1870	1945	2015	2090					
40 km/h		1400	1470	1540	1605	1675	1745	1815	1880	1950					
50 km/h				1400	1465	1535	1600	1665	1735	1800					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
24	420/85R24 142A8/139B TL			875390	460	1329	598	3949	DW15L	DW14L W14L W15L	710	228	42		
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1970	2165	2265	2365	2465	2560	2660	2760	2860	2955	3155	3450	3645	3780	3975
30 km/h	1600	1770	1860	1945	2030	2115	2200	2290	2375	2460	2555	2695	2835		
40 km/h		1660	1740	1820	1900	1980	2060	2140	2220	2300	2390	2520	2650		
50 km/h				1650	1730	1805	1885	1965	2040	2120	2195	2300	2410		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	250/85R28 112A8/109B TL			162161	247	1142	520	3403	W8		W7		725	75	37
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	960	1055	1105	1150	1200	1250	1295	1345	1390	1440	1535	1680			
30 km/h	780	865	905	950	990	1030	1075	1115	1160	1200					
40 km/h		810	850	890	925	965	1005	1045	1080	1120					
50 km/h				800	840	875	915	955	990	1030					

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	280/85R28 118A8/115B TL <i>11.2 R28</i>	161885	297	1200	543	3571	W10		W9		725	100	39
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1130	1245	1300	1355	1415	1470	1525	1585	1640	1695	1810	1980	
30 km/h	920	1020	1065	1115	1165	1215	1265	1310	1360	1410			
40 km/h		950	995	1045	1090	1135	1180	1230	1275	1320			
50 km/h			950	995	1040	1085	1130	1175	1220				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	320/85R28 124A8/121B TL <i>12.4 R28</i>	161772	322	1253	562	3721	W11		W10		726	134	42
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1370	1505	1575	1645	1715	1780	1850	1920	1990	2055	2195	2400	
30 km/h	1110	1230	1290	1350	1410	1470	1530	1590	1650	1710			
40 km/h		1150	1205	1265	1320	1375	1430	1490	1545	1600			
50 km/h			1130	1185	1235	1290	1345	1395	1450				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	340/85R28 127A8/124B TL <i>13.6 R28</i>	161773	363	1307	586	3882	W12		W11 W12L		732	155	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1500	1650	1725	1800	1875	1950	2025	2105	2180	2255	2405	2630	
30 km/h	1220	1350	1415	1480	1545	1610	1675	1740	1805	1870			
40 km/h		1260	1320	1385	1445	1505	1565	1630	1690	1750			
50 km/h			1250	1310	1365	1425	1485	1540	1600				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	380/85R28 133A8/130B TL <i>14.9 R28</i>	161774	391	1360	607	4034	W13		W11 W12		821	204	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1760	1935	2025	2115	2205	2290	2380	2470	2560	2645	2825	3090	
30 km/h	1430	1585	1660	1740	1815	1890	1970	2045	2125	2200			
40 km/h		1480	1555	1625	1700	1770	1845	1915	1990	2060			
50 km/h			1480	1550	1620	1690	1760	1830	1900				

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
28	420/85R28 144A8/141B TL 16.9 R28			955665	458	1435	647	4267	DW15L	DW14L W14L W15L	822	251	47		
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2080	2290	2395	2500	2605	2710	2815	2915	3020	3125	3335	3650	3855	3995	4200
30 km/h	1690	1870	1965	2055	2145	2235	2325	2420	2510	2600	2700	2850	3000		
40 km/h		1750	1835	1920	2005	2090	2175	2260	2345	2430	2525	2660	2800		
50 km/h				1750	1830	1915	1995	2075	2160	2240	2320	2435	2550		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	380/85R30 135A8/132B TL 14.9 R30			161886	396	1413	628	4188	W13	W12	734	215	43
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1860	2050	2140	2235	2330	2425	2520	2610	2705	2800	2990	3270	
30 km/h	1520	1680	1765	1845	1925	2005	2085	2170	2250	2330			
40 km/h		1570	1645	1725	1800	1875	1950	2030	2105	2180			
50 km/h				1560	1635	1705	1780	1855	1925	2000			

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	420/85R30 140A8/137B TL 16.9 R30			161776	447	1474	657	4371	DW15L		DW14L W14L W15L		754	263	48
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	2140	2355	2460	2570	2675	2785	2890	3000	3105	3215	3430	3750			
30 km/h	1740	1930	2020	2115	2210	2305	2400	2490	2585	2680					
40 km/h		1800	1890	1975	2065	2150	2240	2325	2415	2500					
50 km/h				1790	1875	1960	2045	2130	2215	2300					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	460/85R30 145A8/142B TL 18.4 R30			161887	478	1547	681	4574	DW16L	DW15L W15L W16L	757	326	50
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	2480	2730	2855	2980	3105	3230	3355	3475	3600	3725	3975	4350	
30 km/h	2020	2235	2345	2450	2560	2670	2775	2885	2990	3100			
40 km/h		2090	2190	2295	2395	2495	2595	2700	2800	2900			
50 km/h				2070	2165	2265	2360	2455	2555	2650			

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
32	320/85R32 126A8/123B TL 12.4 R32			161888	330	1356	615	4037	W11		W10		760	153	40
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1450	1595	1670	1745	1815	1890	1965	2035	2110	2185	2330	2550			
30 km/h	1180	1310	1370	1435	1500	1565	1630	1690	1755	1820					
40 km/h		1220	1280	1340	1400	1460	1520	1580	1640	1700					
50 km/h				1210	1265	1325	1380	1435	1495	1550					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	420/85R34 142A8/139B TL 16.9 R34			161777	442	1581	708	4693	DW15L		DW14L W14L W15L		704	293	46
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	2270	2500	2610	2725	2840	2955	3070	3180	3295	3410	3640	3980			
30 km/h	1840	2040	2140	2240	2340	2440	2540	2640	2740	2840					
40 km/h	1910		2005	2095	2190	2280	2375	2465	2560	2650					
50 km/h				1900	1990	2075	2165	2255	2340	2430					

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	460/85R34 147A8/144B TL 18.4 R34			161778	488	1659	737	4916	DW16L		DW15L W15L W16L	823	355	50
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1		
Psi	9	12	13	15	16	17	19	20	22	23	26	30		
10 km/h	2630	2895	3025	3160	3290	3420	3555	3685	3820	3950	4215	4610		
30 km/h	2140	2370	2485	2600	2715	2830	2945	3060	3175	3290				
40 km/h		2210	2320	2430	2535	2645	2755	2865	2970	3080				
50 km/h				2180	2285	2385	2490	2595	2695	2800				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
36	320/85R36 128A8/125B TL 12.4 R36			161779	323	1461	667	4357	W11		W10		779	165	43
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1			
Psi	9	12	13	15	16	17	19	20	22	23	26	30			
10 km/h	1540	1695	1770	1850	1925	2005	2080	2160	2235	2315	2470	2700			
30 km/h	1250	1385	1455	1520	1590	1660	1725	1795	1860	1930					
40 km/h		1300	1365	1425	1490	1550	1615	1675	1740	1800					
50 km/h				1290	1350	1410	1470	1530	1590	1650					

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
36	340/85R36 132A8/129B TL 13.6 R36	161780	354	1503	684	4478	W12		W11		780	192	43
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1710	1880	1970	2055	2140	2225	2310	2400	2485	2570	2740	3000	
30 km/h	1390	1540	1615	1690	1765	1840	1915	1990	2065	2140			
40 km/h		1440	1510	1580	1650	1720	1790	1860	1930	2000			
50 km/h			1440	1510	1575	1645	1715	1780	1850				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	340/85R38 133A8/130B TL 13.6 R38	161781	361	1563	714	4661	W12		W11		795	194	46
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	1760	1935	2025	2115	2205	2290	2380	2470	2560	2645	2825	3090	
30 km/h	1430	1585	1660	1740	1815	1890	1970	2045	2125	2200			
40 km/h		1480	1555	1625	1700	1770	1845	1915	1990	2060			
50 km/h			1480	1550	1620	1690	1760	1830	1900				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	420/85R38 144A8/141B TL 16.9 R38	161782	445	1665	748	4947	DW15L		DW14L W14L W15L		786	323	48
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	
10 km/h	2390	2630	2750	2875	2995	3115	3235	3355	3475	3595	3840	4200	
30 km/h	1950	2160	2265	2370	2475	2580	2685	2790	2895	3000			
40 km/h		2020	2120	2215	2315	2410	2510	2605	2705	2800			
50 km/h			2010	2105	2200	2295	2390	2485	2580				
max 40 km/h FRT			2425	2540	2660	2775	2895	3010	3125	3360			

* Refer to the notes at the end of the tables of this range

KLEBER TRAKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	460/85R38 149A8/146B TL 18.4 R38				161783	488	1754	786	5208	DW16L		DW15L W15L W16L	824	383	50	
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1				
Psi	9	12	13	15	16	17	19	20	22	23	26	30				
10 km/h	2780	3060	3200	3340	3480	3620	3760	3900	4040	4180	4460	4880				
30 km/h	2260	2505	2625	2750	2870	2990	3115	3235	3360	3480						
40 km/h		2340	2455	2570	2680	2795	2910	3025	3135	3250						
50 km/h				2340	2450	2560	2670	2780	2890	3000						
max 40 km/h FRT				2810	2945	3085	3220	3355	3490	3630	3900					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
38	520/85R38 155A8/152B TL 20.8 R38				161784	541	1838	820	5452	DW18L		DW16L W16L W18L	825	518	56	
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1				
Psi	9	12	13	15	16	17	19	20	22	23	26	30				
10 km/h	3310	3645	3810	3975	4145	4310	4475	4645	4810	4975	5310	5810				
30 km/h	2700	2990	3135	3280	3425	3570	3715	3860	4005	4150						
40 km/h		2790	2925	3065	3200	3335	3470	3610	3745	3880						
50 km/h				2770	2900	3030	3160	3290	3420	3550						
max 40 km/h FRT				3350	3515	3680	3840	4005	4170	4335	4660					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
42	520/85R42 157A8/157B TL 20.8 R42				656000	557	1948	867	5776	DW18L		DW16L W18L W16L	802	545	52	
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1				
Psi	9	12	13	15	16	17	19	20	22	23	26	30				
10 km/h	3520	3875	4055	4230	4410	4590	4765	4945	5120	5300	5655	6190				
30 km/h	2870	3180	3330	3485	3640	3795	3950	4100	4255	4410						
40 km/h		2970	3115	3260	3405	3550	3690	3835	3980	4125						
50 km/h				3260	3405	3550	3695	3835	3980	4125						
max 40 km/h FRT				3565	3740	3910	4085	4260	4430	4605	4950					

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER SUPER VIGNE

Tyres designed for viticulture.

✓ PROTECTS PLANT COVER

- Tread pattern designed for vineyards and orchards.

✓ ROBUSTNESS

- Rubber and casing that resist cuts and tears.

SIZES

7.50R16 100A8 TL
7.50R18 102A8 TL
7.50R20 104A8 TL
9.5R20 108A8 TL
11.2R20 111A8 TL

8.3R24 106A8 TL
9.5R24 107A8 TL
11.2R24 114A8 TL
13.6R24 121A8 TL
14.9R24 126A8 TL

9.5R28 109A8 TL
11.2R28 116A8 TL
12.4R28 121A8 TL
13.6R28 123A8 TL
14.9R28 128A8 TL

KLEBER SUPER VIGNE

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
16	7.50R16 100A8 TL			460305	200	796	357	2388	5.50F				317 431	32	25
Bar	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9	3.2	3.5		
Psi	15	17	19	20	22	23	26	30	35	38	42	46	51		
10 km/h						670	760	890	1020	1055	1100	1150	1200		
30 km/h	430	475	500	525	545	570	605	660	715	750	805	860			
40 km/h						520	555	610	660	695	750	800			

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
18	7.50R18 102A8 TL				574346	200	854	394	2553	5.50F				440 441	34	25
Bar	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9	3.2	3.5			
Psi	15	17	19	20	22	23	26	30	35	38	42	46	51			
10 km/h						710	805	940	1080	1115	1170	1225	1280			
30 km/h	450	505	530	555	585	610	650	705	760	800	855	910				
40 km/h						550	590	645	700	740	795	850				

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	7.50R20 104A8 TL			401887	200	904	409	2718	5.50F				655 660	44	25
Bar	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9	3.2	3.5		
Psi	15	17	19	20	22	23	26	30	35	38	42	46	51		
10 km/h						750	850	1000	1150	1185	1240	1295	1350		
30 km/h	480	535	565	595	620	650	690	745	805	845	900	960			
40 km/h						590	630	685	745	785	840	900			

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	9.5R20 108A8 TL				283935	245	938	437	2811	W8	W7	533	59	27
Bar	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9	3.2	3.5	
Psi	15	17	19	20	22	23	26	30	35	38	42	46	51	
10 km/h						830	945	1110	1280	1320	1380	1440	1500	
30 km/h	540	600	630	660	690	720	765	830	895	940	1005	1070		
40 km/h						650	695	760	825	870	935	1000		

* Refer to the notes at the end of the tables of this range

KLEBER SUPER VIGNE

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	11.2R20 111A8 TL	963152	288	983	440	2918	W9	W8 W10	542	74	28
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1100	1200	1245	1295	1345	1395	1495	1640	
30 km/h	780	860	935	1015	1055	1090	1130	1170			
40 km/h			870	945	980	1015	1055	1090			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	8.3R24 106A8 TL	257555	210	984	454	2951	W7		686	49	25
Bar	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.6	2.9	3.2
Psi	17	19	20	22	23	26	30	35	38	42	46
10 km/h					790	895	1055	1210	1250	1310	1370
30 km/h	570	600	625	655	680	725	785	850	895	955	1020
40 km/h					620	665	725	790	830	890	950

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	9.5R24 107A8 TL	571677	240	1027	463	3053	W8	W7	686	60	33
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			990	1075	1120	1160	1205	1245	1330	1460	
30 km/h	690	760	830	900	935	970	1005	1040			
40 km/h			780	845	880	915	945	980			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	11.2R24 114A8 TL	162123	297	1084	488	3250	W10	W9		89	36
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1190	1295	1350	1400	1455	1505	1610	1770	
30 km/h	840	925	1010	1090	1135	1175	1220	1260			
40 km/h			940	1020	1060	1100	1140	1180			

* Refer to the notes at the end of the tables of this range

KLEBER SUPER VIGNE

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	13.6R24 121A8 TL	162125	356	1188	534	3577	W12	W11	700	143	40
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1470	1600	1665	1730	1795	1855	1985	2180	
30 km/h	1030	1135	1240	1340	1395	1445	1500	1550			
40 km/h			1160	1255	1305	1355	1400	1450			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	14.9R24 126A8 TL	162167	383	1241	551	3678	W13	W12	703	174	38
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1640	1805	1890	1970	2055	2135	2300	2550	
30 km/h	1160	1290	1425	1555	1620	1690	1755	1820			
40 km/h		1200	1325	1450	1515	1575	1640	1700			
50 km/h			1180	1305	1365	1425	1490	1550			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	9.5R28 109A8 TL	188404	235	1128	527	3364	W8	W7	725	76	34
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1040	1135	1180	1225	1270	1320	1410	1550	
30 km/h	730	805	880	950	990	1025	1065	1100			
40 km/h			820	890	925	960	995	1030			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	11.2R28 116A8 TL	162127	290	1191	540	3545	W10	W9	725	98	36
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h			1270	1380	1435	1490	1545	1605	1715	1880	
30 km/h	890	980	1070	1160	1205	1250	1295	1340			
40 km/h			1000	1085	1125	1165	1210	1250			

* Refer to the notes at the end of the tables of this range

KLEBER SUPER VIGNE

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	12.4R28 121A8 TL	162128	335	1258	568	3720	W11	W8 W9	726	122	35
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h		1470	1600	1665	1730	1795	1855	1985	2180		
30 km/h	1030	1135	1240	1340	1395	1445	1500	1550			
40 km/h		1160	1255	1305	1355	1400	1450				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	13.6R28 123A8 TL	162129	362	1280	577	3806	W12	W11	732	150	37
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h		1570	1710	1775	1845	1915	1985	2125	2330		
30 km/h	1100	1210	1325	1435	1490	1550	1605	1660			
40 km/h		1240	1345	1395	1445	1500	1550				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	14.9R28 128A8 TL	162166	382	1348	603	4025	W13	W12 W13	821	197	37
Bar	0.6	0.8	1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	
Psi	9	12	15	17	19	20	22	23	26	30	
10 km/h		1730	1905	1995	2085	2170	2260	2435	2700		
30 km/h	1220	1360	1505	1645	1715	1790	1860	1930			
40 km/h		1270	1405	1535	1600	1670	1735	1800			
50 km/h			1240	1375	1440	1505	1575	1640			

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER SUPER 8L

Tyres designed for viticulture.

- ✓ **LONG TYRE LIFE**
- ✓ **VERSATILITY**
- ✓ **RELIABILITY AND EFFICIENCY**

SIZES

260/70R16 109A8/106B TL
280/70R16 112A8/109B TL
300/70R20 119A8/116B TL
320/70R20 123A8/120B TL
360/70R20 129A8/126B TL
420/70R30 134A8/131B TL

KLEBER SUPER 8L

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
16	260/70R16 109A8/106B TL				161811	256	776	348	2304	W8		W9		184	45	29
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41	
10 km/h	520	615	660	705	755	800	850	895	940	990	1080	1220	1365	1505	1550	
30 km/h	440	515	550	585	625	660	695	735	770	805	880	990	1100			
40 km/h	410	480	515	550	580	615	650	685	720	755	825	925	1030			
50 km/h		445	475	505	535	565	595	625	655	685	745	835	925			

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
16	280/70R16 112A8/109B TL			161686	276	805	361	2404	W9		W10L W8L W8	184	50	29	
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	580	680	730	780	830	880	930	980	1030	1080	1180	1330	1480	1630	1680
30 km/h	490	570	610	650	685	725	765	805	845	885	965	1080	1200		
40 km/h	460	535	570	605	645	680	715	755	790	825	900	1010	1120		
50 km/h		490	525	560	590	625	660	695	725	760	830	930	1030		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	300/70R20 119A8/116B TL			161414	292	960	431	2852	W9		W8 W10		542	71	31
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	710	830	890	950	1010	1075	1135	1195	1255	1315	1435	1615	1800	1980	2040
30 km/h	620	715	760	805	855	900	945	995	1040	1085	1180	1320	1460		
40 km/h	580	665	710	755	795	840	885	925	970	1015	1100	1230	1360		
50 km/h		610	650	690	730	770	810	850	890	930	1010	1130	1250		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	320/70R20 123A8/120B TL			161740	315	990	442	2934	W10		W9 W11		542	83	32
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41
10 km/h	800	940	1010	1080	1150	1215	1285	1355	1425	1495	1635	1845	2050	2260	2330
30 km/h	670	780	835	890	945	1000	1055	1110	1165	1220	1330	1495	1660		
40 km/h	630	730	785	835	885	935	990	1040	1090	1140	1245	1395	1550		
50 km/h		670	715	760	805	855	900	945	990	1035	1125	1265	1400		

* Refer to the notes at the end of the tables of this range

KLEBER SUPER 8L

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	360/70R20 129A8/126B TL				161867	358	1062	470	3144	W11		W9 W10 W12		664	108	41
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1	2.4	2.7	2.8	
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	39	41	
10 km/h	950	1115	1200	1285	1365	1450	1530	1615	1700	1780	1950	2200	2445	2695	2780	
30 km/h	800	930	995	1060	1130	1195	1260	1325	1390	1455	1585	1785	1980			
40 km/h	750	870	935	995	1055	1115	1180	1240	1300	1360	1485	1665	1850			
50 km/h		800	855	915	970	1025	1080	1140	1195	1250	1365	1530	1700			

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	420/70R30 134A8/131B TL				161033	420	1412	638	4202	W13		W12 DW14L W14		734	205	41
Bar	0.6	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.8	2.1				
Psi	9	12	13	15	16	17	19	20	22	23	26	30				
10 km/h	1460	1690	1805	1920	2035	2150	2265	2375	2490	2605	2835	3180				
30 km/h	1230	1440	1540	1645	1750	1855	1960	2060	2165	2270						
40 km/h	1150	1345	1440	1540	1635	1730	1830	1925	2025	2120						
50 km/h		1250	1340	1425	1515	1600	1690	1775	1865	1950						

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER SUPER G

The tyre that protects
your pastures.

✓ PROTECTS PASTURES

- Wide rounded lugs help reduce damage to the grass.

✓ WORKING ON SLOPES

- Special shoulder design to maximise hold on slopes.

SIZES

340/75R20 117A8/114B TT

14.9LR20 119A8/116B TL

16.9R30 137A8/134B TL

KLEBER SUPER G

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	340/75R20 117A8/114B TT				160884	333	1045	470	3114	W11				664	113	29
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.1	
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	30	
10 km/h					1150	1220	1290	1365	1435	1505	1575	1645	1715	1790	1930	
30 km/h	730	795	860	920	985	1050	1115	1180	1240	1305	1370					
40 km/h	670	730	795	855	920	980	1040	1105	1165	1230	1290					
50 km/h					840	895	955	1010	1065	1125	1180					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
20	14.9LR20 119A8/1168 TL				286656	390	1092	491	3246	13	W11 W12	664	130	30		
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.1	
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	30	
10 km/h						1210	1285	1360	1435	1510	1585	1665	1740	1815	1890	2040
30 km/h	770	840	910	975	1045	1115	1185	1255	1320	1390	1460					
40 km/h	710	775	840	905	970	1035	1100	1165	1230	1295	1360					
50 km/h					890	950	1010	1070	1130	1190	1250					

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
30	16.9R30 137A8/134B TL				450712	439	1470	657	4362	DW15L	DW14L W14L W15L	754	263	32	
Bar	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.1
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26	28	30
10 km/h					2050	2175	2305	2430	2560	2685	2815	2940	3070	3195	3450
30 km/h	1300	1415	1530	1650	1765	1880	1995	2110	2230	2345	2460				
40 km/h	1210	1320	1430	1535	1645	1755	1865	1975	2080	2190	2300				
50 km/h					1520	1620	1720	1820	1920	2020	2120				

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For ploughing and other field applications subject to high torque, use the 30 km/h line.
- When using single tyre configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50% of time on road.
- 10 km/h LT (Low Torque) (max speed 10 km/h).



KLEBER CROPKER

The narrow tyre designed
for crop protection

✓ PRODUCTIVITY

- Excellent traction thanks to optimal tread pattern and architecture
- Improved self-cleaning with this new generation of tread pattern.

✓ HIGH QUALITY CROP PROTECTION

- Improved plant protection.

✓ ROBUSTNESS AND LONGEVITY

- Improved casing, surpass former Kleber Super 3.

SIZES

230/95R32 128D/131A8 TL

270/95R32 136D/139A8 TL

230/95R36 130D/133A8 TL

270/95R36 139D/142A8 TL

270/95R38 140D/143A8 TL

230/95R40 132D/135A8 TL

270/95R42 141D/144A8 TL

300/95R42 147D/150A8 TL

230/95R44 134D/137A8 TL

270/95R44 142D/145A8 TL

300/95R46 148D/151A8 TL

230/95R48 136D/139A8 TL

270/95R48 144D/147A8 TL

300/95R52 151D/154A8 TL

270/95R54 146D/149A8 TL

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
32	230/95R32 128D/131A8 TL 9.5 R 32			002322	225	1256	587	3768	W7		W8		758	66	31
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	1615	1785	1955	2045	2135	2220	2310	2405	2505	2600	2695	2795	2890	2975	3060
25 km/h Cyc	1405	1470	1535	1595	1660	1730	1800	1870	1935	2005	2075	2135	2195		
30 km/h	1325	1385	1445	1505	1565	1630	1695	1760	1825	1890	1955	2015	2070		
40 km/h	1260	1320	1375	1435	1490	1550	1615	1675	1735	1800	1860	1915	1970		
40 km/h FRT															2160
50 km/h	1210	1265	1320	1375	1430	1490	1550	1610	1665	1725	1785	1840	1890		
50 km/h FRT															1960
65 km/h	1150	1205	1255	1310	1360	1415	1475	1530	1585	1645	1700	1750	1800		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
32	270/95R32 136D/139A8 TL 11.2 R 32			227326	276	1320	617	3957	W9		W8 W10		763	101	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2005	2235	2465	2570	2680	2785	2890	3010	3130	3250	3365	3485	3605	3710	3810
25 km/h Cyc	1770	1845	1925	2000	2075	2160	2245	2330	2415	2500	2585	2660	2735		
30 km/h	1670	1740	1815	1885	1955	2035	2115	2200	2280	2360	2440	2510	2575		
40 km/h	1590	1660	1725	1795	1860	1935	2015	2090	2165	2245	2320	2390	2455		
40 km/h FRT															2690
50 km/h	1525	1590	1655	1720	1785	1860	1930	2005	2080	2150	2225	2290	2350		
50 km/h FRT															2440
65 km/h	1450	1515	1575	1640	1700	1770	1840	1910	1980	2050	2120	2180	2240		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
36	230/95R36 130D/133A8 TL 9.5 R 36			239482	224	1335	623	4003	W7		W8		779	87	31
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	1700	1845	1985	2130	2270	2370	2470	2570	2665	2765	2865	2965	3060	3145	3230
25 km/h Cyc	1480	1555	1625	1700	1770	1840	1910	1985	2055	2125	2195	2260	2320		
30 km/h	1395	1465	1535	1600	1670	1735	1805	1870	1935	2005	2070	2130	2185		
40 km/h	1330	1395	1460	1525	1590	1655	1715	1780	1845	1905	1970	2025	2080		
40 km/h FRT															2280
50 km/h	1275	1340	1400	1465	1525	1585	1645	1710	1770	1830	1890	1945	1995		
50 km/h FRT															2070
65 km/h	1215	1275	1335	1390	1450	1510	1565	1625	1685	1740	1800	1850	1900		

* Refer to the notes at the end of the tables of this range

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
36	270/95R36 139D/142A8 TL 11.2 R 36				659295	260	1415	651	4207	W9		W8 W10	779	121	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2185	2350	2520	2685	2850	2980	3110	3240	3370	3500	3630	3770	3910	4020	4130
25 km/h Cyc	1890	1965	2045	2120	2195	2295	2400	2500	2600	2705	2805	2885	2965		
30 km/h	1785	1855	1930	2000	2070	2165	2260	2360	2455	2550	2645	2720	2795		
40 km/h	1695	1765	1835	1900	1970	2060	2155	2245	2335	2430	2520	2590	2660		
40 km/h FRT															2915
50 km/h	1630	1695	1760	1825	1890	1980	2065	2155	2240	2330	2415	2485	2550		
50 km/h FRT															2650
65 km/h	1550	1615	1675	1740	1800	1885	1965	2050	2135	2215	2300	2365	2430		

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	270/95R38 140D/143A8 TL 11.2 R 38				559899	274	1469	677	4410	W9		W8 W10		779	125	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4	
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
10 km/h Cyc	2245	2485	2720	2825	2935	3040	3145	3290	3435	3580	3720	3865	4010	4130	4250	
25 km/h Cyc	1950	2025	2105	2180	2255	2360	2465	2570	2670	2775	2880	2965	3050			
30 km/h	1840	1915	1985	2060	2130	2230	2325	2425	2520	2620	2715	2795	2875			
40 km/h	1750	1820	1890	1955	2025	2120	2210	2305	2400	2490	2585	2665	2740			
40 km/h FRT															3000	
50 km/h	1680	1745	1815	1880	1945	2035	2125	2215	2300	2390	2480	2555	2625			
50 km/h FRT															2725	
65 km/h	1600	1665	1725	1790	1850	1935	2020	2105	2190	2275	2360	2430	2500			

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
40	230/95R40 132D/135A8 TL 9.5 R 40				265784	223	1446	675	4311	W7		W8		92	31
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	1800	1945	2085	2230	2370	2475	2580	2685	2790	2895	3000	3115	3230	3315	3400
25 km/h Cyc	1570	1635	1700	1765	1830	1910	1995	2075	2155	2240	2320	2380	2440		
30 km/h	1480	1540	1605	1665	1725	1800	1880	1955	2030	2110	2185	2245	2300		
40 km/h	1405	1465	1525	1585	1645	1720	1790	1865	1935	2010	2080	2135	2190		
40 km/h FRT															2400
50 km/h	1350	1405	1465	1520	1575	1645	1715	1785	1855	1925	1995	2050	2100		
50 km/h FRT															2180
65 km/h	1285	1340	1395	1445	1500	1565	1635	1700	1765	1835	1900	1950	2000		

* Refer to the notes at the end of the tables of this range

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	270/95R42 141D/144A8 TL 11.2 R 42			502916	287	1563	745	4690	W9		W8 W10			122	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2310	2510	2710	2905	3105	3245	3380	3520	3660	3795	3935	4095	4250	4315	4380
25 km/h Cyc	2075	2150	2230	2305	2380	2490	2605	2715	2825	2940	3050	3095	3140		
30 km/h	1955	2030	2100	2175	2245	2350	2455	2560	2665	2770	2875	2920	2960		
40 km/h	1860	1930	2000	2065	2135	2235	2335	2440	2540	2640	2740	2780	2820		
40 km/h FRT															3090
50 km/h	1785	1850	1920	1985	2050	2145	2240	2340	2435	2530	2625	2665	2705		
50 km/h FRT															2810
65 km/h	1700	1765	1825	1890	1950	2040	2135	2225	2315	2410	2500	2540	2575		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	300/95R42 147D/150A8 TL 12.4 R 42			349230	309.3	1627	762	4866	W9		W8 W10			155	35
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2720	2945	3170	3390	3615	3780	3940	4105	4265	4430	4590	4760	4930	5080	5230
25 km/h Cyc	2380	2485	2595	2700	2805	2930	3050	3175	3295	3420	3540	3645	3750		
30 km/h	2245	2345	2445	2545	2645	2760	2875	2990	3105	3220	3335	3435	3535		
40 km/h	2135	2230	2330	2425	2520	2630	2740	2850	2955	3065	3175	3270	3365		
40 km/h FRT															3690
50 km/h	2050	2140	2235	2325	2415	2520	2625	2730	2835	2940	3045	3140	3230		
50 km/h FRT															3350
65 km/h	1950	2040	2125	2215	2300	2400	2500	2600	2700	2800	2900	2990	3075		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
44	230/95R44 134D/137A8 TL 9.5 R 44			625299	219.1	1547	728	4645	W7		W8			102	31
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	1905	2060	2210	2365	2515	2625	2735	2845	2950	3060	3170	3285	3400	3505	3605
25 km/h Cyc	1660	1735	1805	1880	1950	2030	2115	2195	2275	2360	2440	2515	2585		
30 km/h	1565	1635	1705	1770	1840	1915	1995	2070	2145	2225	2300	2370	2440		
40 km/h	1490	1555	1620	1685	1750	1825	1895	1970	2045	2115	2190	2255	2320		
40 km/h FRT															2545
50 km/h	1430	1495	1555	1620	1680	1750	1820	1890	1960	2030	2100	2165	2225		
50 km/h FRT															2310
65 km/h	1360	1420	1480	1540	1600	1665	1735	1800	1865	1935	2000	2060	2120		

* Refer to the notes at the end of the tables of this range

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
44	270/95R44 142D/145A8 TL 11.2 R 44				699532	287	1619	768	4856	W9		W8 W10	813	144	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2380	2570	2765	2955	3145	3295	3450	3600	3750	3905	4055	4220	4380	4445	4505
25 km/h Cyc	2075	2165	2260	2350	2440	2555	2675	2790	2905	3025	3140	3190	3235		
30 km/h	1955	2040	2130	2215	2300	2410	2520	2630	2740	2850	2960	3005	3050		
40 km/h	1860	1945	2025	2110	2190	2295	2400	2505	2610	2715	2820	2860	2900		
40 km/h FRT															3180
50 km/h	1785	1865	1945	2020	2100	2200	2300	2405	2505	2605	2705	2745	2785		
50 km/h FRT															2890
65 km/h	1700	1775	1850	1925	2000	2095	2190	2290	2385	2480	2575	2615	2650		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
46	300/95R46 148D/151A8 TL 12.4 R 52			097180	299	1734	813	5203	W9		W8 W10		835	191	35
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2890	3195	3500	3660	3815	3975	4130	4290	4455	4615	4775	4940	5100	5230	5355
25 km/h Cyc	2515	2630	2740	2855	2965	3080	3195	3315	3430	3545	3660	3755	3845		
30 km/h	2370	2475	2585	2690	2795	2905	3015	3125	3230	3340	3450	3540	3625		
40 km/h	2255	2355	2460	2560	2660	2765	2870	2975	3075	3180	3285	3370	3450		
40 km/h FRT															3780
50 km/h	2165	2260	2360	2455	2550	2650	2750	2850	2950	3050	3150	3230	3310		
50 km/h FRT															3435
65 km/h	2060	2155	2245	2340	2430	2525	2620	2715	2810	2905	3000	3075	3150		

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
48	230/95R48 136D/139A8 TL 9.5 R 48				973505	224	1659	786	4989	W7		W8	835	109	31
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2005	2235	2465	2570	2680	2785	2890	3010	3130	3250	3365	3485	3605	3710	3810
25 km/h Cyc	1770	1845	1925	2000	2075	2160	2245	2330	2415	2500	2585	2660	2735		
30 km/h	1670	1740	1815	1885	1955	2035	2115	2200	2280	2360	2440	2510	2575		
40 km/h	1590	1660	1725	1795	1860	1935	2015	2090	2165	2245	2320	2390	2455		
40 km/h FRT															2690
50 km/h	1525	1590	1655	1720	1785	1860	1930	2005	2080	2150	2225	2290	2350		
50 km/h FRT															2440
65 km/h	1450	1515	1575	1640	1700	1770	1840	1910	1980	2050	2120	2180	2240		

* Refer to the notes at the end of the tables of this range

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
48	270/95R48 144D/147A8 TL 11.2 R 48			199409	277	1736	819	5217	W9		W8 W10		835	130	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2550	2745	2940	3135	3330	3475	3620	3770	3915	4060	4205	4355	4505	4630	4760
25 km/h Cyc	2195	2295	2390	2490	2585	2695	2800	2910	3020	3125	3235	3325	3415		
30 km/h	2070	2165	2255	2350	2440	2540	2645	2745	2845	2950	3050	3135	3220		
40 km/h	1970	2060	2145	2235	2320	2415	2515	2610	2705	2805	2900	2985	3065		
40 km/h FRT															3360
50 km/h	1890	1975	2060	2140	2225	2320	2410	2505	2600	2690	2785	2865	2940		
50 km/h FRT															3050
65 km/h	1800	1880	1960	2040	2120	2210	2295	2385	2475	2560	2650	2725	2800		

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
52	300/95R52 151D/154A8 TL 12.4 R 52			747425	297	1886	888	5664	W9		W10 W8		816	182	35
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	3060	3385	3705	3875	4045	4210	4380	4570	4760	4955	5145	5335	5525	5695	5865
25 km/h Cyc	2660	2780	2900	3020	3140	3280	3415	3555	3690	3830	3965	4090	4210		
30 km/h	2505	2620	2735	2845	2960	3090	3220	3350	3480	3610	3740	3855	3970		
40 km/h	2385	2495	2605	2710	2820	2945	3065	3190	3315	3435	3560	3670	3780		
40 km/h FRT															4140
50 km/h	2290	2395	2500	2600	2705	2825	2940	3060	3180	3295	3415	3520	3625		
50 km/h FRT															3760
65 km/h	2180	2280	2380	2475	2575	2690	2800	2915	3025	3140	3250	3350	3450		

Ø inches	Description				CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
54	270/95R54 146D/149A8 TL <i>11.2 R 54</i>				718149	275	1887	896	5679	W9		W8 W10	816	174	33
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2720	3020	3315	3440	3565	3685	3810	3970	4125	4285	4445	4600	4760	4930	5100
25 km/h Cyc	2380	2470	2560	2645	2735	2850	2960	3075	3190	3300	3415	3540	3660		
30 km/h	2245	2330	2410	2495	2575	2685	2790	2900	3005	3115	3220	3335	3450		
40 km/h	2135	2215	2295	2375	2455	2555	2660	2760	2860	2965	3065	3175	3285		
40 km/h FRT															3600
50 km/h	2050	2125	2200	2275	2350	2450	2545	2645	2745	2840	2940	3045	3150		
50 km/h FRT															3270
65 km/h	1950	2025	2095	2170	2240	2335	2425	2520	2615	2705	2800	2900	3000		

* Refer to the notes at the end of the tables of this range

KLEBER CROPKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For use on slopes of more than 20%, add 0.4 bar
- For intensive road use exceeding 50% time on road, add 0.4 bar
- Use 10, 25 or 30 km/h cyclic loading tables for field use only, travel with full load not to exceed 1,5 km
- FRT: Free Rolling Tyre



KLEBER SUPER 3

A high quality row crop tyre
designed to protect your crops.

✓ ROBUSTNESS AND LONGEVITY

- High load capacity
- Good self cleaning

✓ OPTIMAL DEVELOPMENT FOR ROW-CROPS

- Shape of shoulder perfectly adapted for plant protection.

SIZES

210/95R32 114A8/114B TL

210/95R44 120A8/120B TL

KLEBER SUPER 3

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
32	210/95R32 114A8/114B TL			231707	212	1212	569	3638	W7		758	67	29
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8						
Psi	23	26	29	32	35	38	41						
10 km/h Cyc	1240	1340	1440	1540	1640	1705	1770						
25 km/h	1110	1160	1210	1260	1310								
30 km/h	1070	1120	1165	1215	1260								
30 km/h Cyc	1140	1195	1245	1300	1350								
40 km/h	1000	1045	1090	1135	1180								
50 km/h	1180												

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
44	210/95R44 120A8/120B TL			169754	216	1534	723	4608	W7			81	29
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8						
Psi	23	26	29	32	35	38	41						
10 km/h Cyc	1460	1590	1720	1850	1980	2040	2100						
25 km/h	1310	1370	1430	1490	1550								
30 km/h	1260	1320	1380	1440	1500								
30 km/h Cyc	1350	1415	1475	1540	1600								
40 km/h	1180	1235	1290	1345	1400								
50 km/h	1400												

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For use on slopes of more than 20%, add 0.4 bar
- For intensive road use exceeding 50% time on road, add 0.4 bar
- Use 10, 25 or 30 km/h cyclic loading tables for field use only, travel with full load not to exceed 1,5 km



KLEBER LUGKER

KLEBER's offer
for telescopic handlers used
for agricultural purposes

✓ OPTIMISED DAMAGE RESISTANCE

- Puncture resistance thanks to two metal crown plies.

✓ GOOD TRACTION CAPABILITY

- Lug angle and special design to optimise traction on soft ground.

✓ VERY GOOD STABILITY

- Thanks to the rigidity of the sidewalls there is less deformation when loaded and therefore greater precision during lifting operations.

SIZES

400/70R20 IND 149A8/149B TL

460/70R24 IND 159A8/159B TL

500/70R24 IND 164A8/164B TL

KLEBER LUGKER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
20	400/70R20 IND 149A8/149B TL			478302	412	1062	480	3160	W13		13	664	139	30	
											14				
											12				
											12SDC				
											13SDC				
											DW13				
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	1910	2120	2335	2545	2760	2970	3180	3395	3605	3820	4030	4245	4455	4670	4880
25 km/h	1730	1885	2045	2200	2355	2510	2670	2825	2980	3140	3295	3455	3610		
30 km/h	1660	1810	1965	2115	2265	2415	2570	2720	2870	3025	3175	3330	3480		
40 km/h	1550	1690	1825	1965	2100	2240	2375	2515	2650	2800	2950	3100	3250		
50 km/h	1550	1690	1825	1965	2100	2240	2375	2515	2650	2800	2950	3100	3250		
Stat	2930	3255	3580	3905	4230	4555	4880	5205	5530	5855	6180	6505	6830	7155	7480

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	460/70R24 IND 159A8/159B TL 17.5 LR 24			968722	469	1240	560	3704	DW15L	14 DW14L DW16L 16		710	217	34	
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2570	2855	3140	3425	3710	3995	4280	4565	4850	5135	5420	5705	5990	6275	6560
25 km/h	2320	2530	2745	2955	3165	3375	3585	3800	4010	4225	4435	4650	4860		
30 km/h	2240	2445	2650	2850	3055	3260	3460	3665	3870	4075	4275	4480	4680		
40 km/h	2120	2310	2505	2695	2885	3075	3270	3460	3650	3830	4015	4195	4375		
50 km/h	2120	2310	2505	2695	2885	3075	3270	3460	3650	3830	4015	4195	4375		
Stat	3940	4375	4815	5250	5690	6125	6560	7000	7435	7875	8310	8750	9185	9625	10060

Ø inches	Description			CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	500/70R24 IND 164A8/164B TL 19.5 LR 24			265461	511	1298	582	3830	DW16L		DW15L 16		710	264	34
Bar	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
Psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
10 km/h Cyc	2930	3255	3585	3910	4240	4565	4890	5220	5545	5875	6200	6525	6850	7175	7500
25 km/h	2650	2890	3135	3375	3615	3855	4100	4340	4580	4825	5065	5310	5550		
30 km/h	2560	2795	3025	3260	3490	3725	3955	4190	4420	4655	4885	5120	5350		
40 km/h	2360	2580	2800	3020	3245	3465	3685	3905	4125	4345	4565	4780	5000		
50 km/h	2360	2580	2800	3020	3245	3465	3685	3905	4125	4345	4565	4780	5000		
Stat	4500	5000	5500	6000	6500	7000	7500	8000	8500	9000	9500	10000	10500	11000	11500

*IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (2020/11). Technical data is subject to change without prior notice.

- For use on side slopes: add 0.4 bar.
- For heavy road use, add 0.4 bar.
- Stat: static load.
- 10 km/h Cyc: max. speed 10 km/h with cyclic load.

NOTES

Notes section with horizontal dotted lines for writing.

NOTES

Notes section with horizontal dotted lines for writing.



AGRICULTURE TYRES TECHNICAL DATABOOK

2022

HEADQUARTERS

Manufacture Française des Pneumatiques MICHELIN

A partnership limited by shares with a capital of €504,000,004

Place des Carmes-Déchaux, 63040 Clermont-Ferrand Cedex 9, France

Tel.: +33(0)4 73 32 20 00

Clermont Ferrand Trade and Companies Registry Number 855 200 507

MAY 2022

<https://agricultural.klebertyres.co.uk>

**Kleber**